



U.S. Department
of Transportation

Research and
Special Programs
Administration

400 Seventh Street, S.W.
Washington, D.C. 20590

DOT-E 7948 (EXTENSION)
FOURTH REVISION April 13, 1987

In accordance with 49 CFR 107.105 of the Department of Transportation (DOT) Hazardous Materials Regulations DOT-E 7948 is hereby extended for the party(ies) listed below by changing the expiration date in paragraph 10 to January 31, 1994. This change is effective from the issue date of this extension. All other terms of the exemption remain unchanged.

This extension applies only to party(ies) listed below based on the application(s) received in accordance with 49 CFR 107.105. This extension constitutes a necessary part of this exemption and must be attached to it.

80 *J. Suzanne Helgeseth*
Alan I. Roberts
Associate Administrator
for Hazardous Materials Safety

FEB 27 1992

(DATE)

Dist: FHWA

EXEMPTION HOLDER

APPLICATION DATE

Erickson, Inc.
Richmond, CA

January 30, 1992



U.S. Department
of Transportation

400 Seventh Street, S.W.
Washington, D.C. 20590

**Research and
Special Programs
Administration**

DOT-E 7948
(FOURTH REVISION)

APR 13 1987

1. Erickson, Incorporated, Richmond, California, is hereby granted an exemption from those provisions of this Department's Hazardous Materials Regulations specified in paragraph 5 below to transport packages prescribed herein of certain flammable, corrosive or poison B materials in commerce subject to the requirements specified herein. This exemption authorizes use of a non-DOT specification cargo tank, and provides no relief from any regulation other than specifically stated.
2. BASIS. This exemption is based on Erickson Incorporated's application dated January 14, 1986, submitted in accordance with 49 CFR 107.105 and the public proceeding thereon.
3. HAZARDOUS MATERIALS (Descriptor and class). Liquid and semi-solid waste material, including mixtures, compatible with the packaging, containing flammable liquids or corrosives or poison B materials, or combinations thereof, classed as flammable liquid, corrosive material or poison B as appropriate.
4. PROPER SHIPPING NAME (49 CFR 172.101). Specific commodity name, or generic description, as appropriate.
5. REGULATION AFFECTED. 49 CFR 173.119(a) and (m), 173.245(a), 173.346(a), 178.340-7, 178.342-5, 178.343-5.
6. MODES OF TRANSPORTATION AUTHORIZED. Motor vehicle.
7. SAFETY CONTROL MEASURES. Packaging prescribed is a non-DOT specification cargo tank designed and constructed by Clark Tank and Manufacturing Company, in full compliance with DOT Specification MC-307 or MC-312 (49 CFR 178.340, 178.342, 178.343) except as follows:

a. The cargo tank must be designed, built, and certified in accordance with Section VIII of the ASME Code to a minimum design pressure as follows:

<u>Basic Cargo Tank Specification</u>	<u>Design Pressure (psig)</u>		<u>Minimum Test Pressure (psig)</u>
	<u>Internal (See Note 1)</u>	<u>External (See Note 2)</u>	
MC 307	25	15	37.5
MC 312	25	15	37.5

Note 1: The design pressure must be at least equal to the maximum pressure used for unloading.

Note 2: Vacuum tanks must have an external design pressure of at least 15 psi.

b. Circumferential reinforcement must comply with 49 CFR 178.340-7 except the maximum unreinforced portion of the shell may exceed 60-inches provided thickness and tensile strength of the shell material in combination with the frame and circumferential reinforcement produces structural integrity at least equal to that prescribed in 49 CFR 178.340-4(b).

c. In place of internal valves prescribed in 49 CFR 178.342-5(a) and 178.343-5(b), each tank may be equipped with one 6-inch maximum diameter bottom outlet with gate, plug or butterfly valve and one optional 4-inch maximum diameter bottom inlet with gate, plug or butterfly valve located near the rear of tank in accordance with Drawing 1268 dated July 16, 1978 on file with the Office of Hazardous Materials Transportation (OHMT). Each outlet and inlet must be equipped with an additional shut-off valve, or a blank flange or a sealing cap at the end of the discharge/loading line.

d. The metal identification plate and the manufacturer's certificate must not be marked to indicate compliance with DOT MC-307 or MC-312 specifications but instead must bear reference to DOT-E 7948.

e. Tanks that are to be used in transporting flammable waste materials must be equipped with a spring loaded relief valve.

8. SPECIAL PROVISIONS.

a. Shippers may use the packaging covered by this exemption pursuant to 49 CFR 173.22a.

b. A copy of this exemption must be carried aboard each motor vehicle used to transport packages covered by this exemption.

c. Each cargo tank must be reinspected and retested once every two years in accordance with 49 CFR 177.824 as prescribed for DOT Specification MC-307 or MC 312 cargo tanks, as appropriate, at one and one-half times the sum of the design pressure plus the static head.

d. Each cargo tank must be plainly marked on the right side near the front, in letters at least two inches high on a contrasting background, "DOT-E 7948."

e. The Manufacturer's Data Report for the first cargo tank fabricated must be submitted to the OHMT prior to initial shipment.

9. REPORTING REQUIREMENTS. Any incident involving loss of contents of the package or cargo tank rollover must be reported to the OHMT as soon as practicable.

10. EXPIRATION DATE. March 31, 1988.

Issued at Washington, D.C.:

sa | J. Suzanne Hedgepeth
Alan I. Roberts

Director
Office of Hazardous Materials Transportation

APR 13 1987

(DATE)

Address all inquiries to: Director, Office of Hazardous Materials Transportation,
Research and Special Programs Administration, U.S. Department of Transportation,
Washington, D.C. 20590. Attention: Exemptions Branch.

Dist: FHWA.