

East Building, PHH-30 1200 New Jersey Avenue S.E. Washington, D.C. 20590

### Pipeline and Hazardous Materials Safety Administration

# DOT-SP 10631 (THIRTEENTH REVISION)

(FOR RENEWAL, SEE 49 CFR § 107.109)

- 1. GRANTEE: (See individual authorization letter)
- 2. PURPOSE AND LIMITATION:
  - a. This special permit authorizes the transportation in commerce of certain hazardous materials as specified in paragraph 6 below in DOT Specification MC338 cargo tanks. This special permit provides no relief from the Hazardous Materials Regulations (HMR) other than as specifically stated herein.
  - b. The safety analyses performed in development of this special permit only considered the hazards and risks associated with transportation in commerce.
  - c. Unless otherwise stated herein, this special permit consists of the special permit authorization letter issued to the grantee together with this document.
- 3. REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-180.
- 4. REGULATIONS FROM WHICH EXEMPTED: 49 CFR §§ 173.243 and 173.244 in that the use of an MC 338 cargo tank motor vehicle is not authorized, except as specified herein.
- 5. <u>BASIS</u>: This special permit is based on the application of the Department of Defense US Army Military Surface Deployment & Distribution Command dated March 5, 2021, submitted in accordance with § 107.105 and the public proceeding thereon.

### 6. HAZARDOUS MATERIALS (49 CFR § 172.101):

Hazardous Materials Description			
Proper Shipping Name	Hazard Class/ Division	Identi- fication Number	Packing Group
Dimethylhydrazine, unsymmetrical	6.1	UN1163	I
Hydrazine, anhydrous	8	UN2029	I
Methylhydrazine	6.1	UN1244	I
Toxic by inhalation liquid, corrosive, n.o.s.	6.1	UN3390	I (Hazard Zone B)
Toxic by inhalation liquid, flammable, n.o.s.	6.1	UN3384	I (Hazard Zone B)

- 7. <u>SAFETY CONTROL MEASURES</u>: Packaging prescribed is a specially designed cargo tank motor vehicle designed and fabricated in conformance with DOT Specification MC 338 (§ 178.338) and as follows:
  - a. Each cargo tank motor vehicle must conform to the following engineering documents on file with the OHMS: Process Engineering, Inc. drawings B-27621, Rev 5 dated January 25, 1991 and C-33146 dated April 25, 1991; and Process Engineering, Inc. product specification Model ST-27SMMH, dated April 15, 1991.
  - b. The minimum design pressure for the cargo tank must be 300 psig.
  - c. Each cargo tank must be constructed to achieve thermal conductance between the inner vessel and the atmosphere of not more than 0.08 Btu per square foot per degree Fahrenheit differential per hour, determined at 60 °F.
  - d. The sliding protective housing must be designed to present no flow restriction to vapor discharged from the pressure relief valve. The pressure relief system must communicate directly with the vapor space inside the manway

# April 23, 2021

- cover. The isolation valve between the pressure relief valve and the vapor space must be locked in the open position except as provided for during maintenance operations on the pressure relief valve.
- e. Outlet and inlet valves must be closed by use of blank flanges to be gas tight at all times while the cargo tank is in transit on public highways.
- f. An emergency closure kit must be provided to control leaks in fittings on the dome cover plate. At a minimum, this kit must be equivalent to the requirements of § 178.337-10(d).
- g. The motor carrier must equip each unit with a fireretardant blanket which must be readily available for use in protecting the cargo tank from heat in event of a tire fire.
- h. Outage and filling limits must be in accordance with the requirements of § 173.24b.
- i. DLA must use the SDDC Transportation Protective Services (TPS) Program for carrier selection.
- j. The hazardous material routes must be generated for each movement using the Defense Table of Official Distance program supported by the Department of Defense (DOD). The routes must be reviewed prior to shipment departure for the safest practicable route, taking into account as a minimum the criteria specified in 49 CFR 397.

## 8. SPECIAL PROVISIONS:

- a. A person who is not a holder of this special permit who receives a package covered by this special permit may reoffer it for transportation provided no modifications or changes are made to the package and it is reoffered for transportation in conformance with this special permit and the HMR.
- b. A current copy of this special permit must be maintained at each facility where the package is offered or reoffered for transportation.

## April 23, 2021

- c. Each tank must be plainly placarded in accordance with 49 CFR Part 172, Subpart F and marked "INHALATION HAZARD" in accordance with § 172.313. In addition, each tank must be marked on the right side near the front, in letters at least two inches high on a contrasting background "DOT-SP 10631".
- d. Each tank must be reinspected and retested in accordance with § 180.407 as required for DOT Specification MC 338 cargo tanks. Test pressure must be one and one-quarter times the maximum allowable working pressure (MAWP). Pneumatic retesting using nonflammable gas (e.g., nitrogen or helium) is authorized.
- e. Prior to and after each loading and unloading operation, each cargo tank must be subjected to the DLA-Energy Inspection Checklists Number 9 and 10. The Inspection Checklists must be retained at the inspection facility for at least two (2) years.
- 9. MODES OF TRANSPORTATION AUTHORIZED: Motor vehicle.
- 10. MODAL REQUIREMENTS: A current copy of this special permit must be carried aboard each motor vehicle used to transport packages covered by this special permit.
- 11. <u>COMPLIANCE</u>: Failure by a person to comply with any of the following may result in suspension or revocation of this special permit and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. 5101 <u>et seq</u>:
  - o All terms and conditions prescribed in this special permit and the Hazardous Materials Regulations, 49 CFR Parts 171-180.
  - o Persons operating under the terms of this special permit must comply with the security plan requirement in Subpart I of Part 172 of the HMR, when applicable.
  - o Registration required by § 107.601  $\underline{\text{et seq.}}$ , when applicable.

Each "Hazmat employee", as defined in § 171.8, who performs a function subject to this special permit must receive training on the requirements and conditions of this special permit in addition to the training required by §§ 172.700 through 172.704.

April 23, 2021

No person may use or apply this special permit, including display of its number, when the special permit has expired or is otherwise no longer in effect.

Under Title VII of the Safe, Accountable, Flexible, Efficient Transportation Equity Act: A Legacy for Users (SAFETEA-LU) - "The Hazardous Materials Safety and Security Reauthorization Act of 2005" (Pub. L. 109-59), 119 Stat. 1144 (August 10, 2005), amended the Federal hazardous materials transportation law by changing the term "exemption" to "special permit" and authorizes a special permit to be granted up to two years for new special permits and up to four years for renewals.

12. REPORTING REQUIREMENTS: Shipments or operations conducted under this special permit are subject to the Hazardous Materials Incident Reporting requirements specified in 49 CFR \$171.15(b) Immediate notice of certain hazardous materials incidents, and \$171.16(b) Detailed hazardous materials incident reports. In addition, the grantee(s) of this special permit must notify the Associate Administrator for Hazardous Materials Safety, in writing, of any incident involving a package, shipment or operation conducted under terms of this special permit.

Issued in Washington, D.C.:

for William Schoonover

Associate Administrator for Hazardous Materials Safety

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Pipeline and Hazardous Material Safety Administration, U.S. Department of Transportation, East Building PHH-30, 1200 New Jersey Avenue, Southeast, Washington, D.C. 20590.

Copies of this special permit may be obtained by accessing the Hazardous Materials Safety Homepage at <a href="http://hazmat.dot.gov/sp app/special permits/spec perm index.htm">http://hazmat.dot.gov/sp app/special permits/spec perm index.htm</a>. Photo reproductions and legible reductions of this special permit are permitted. Any alteration of this special permit is prohibited.

PO: MAJORS