

November 03, 2017



U.S. Department
of Transportation

East Building, PHH-30
1200 New Jersey Avenue S.E.
Washington, D.C. 20590

**Pipeline and Hazardous
Materials Safety Administration**

DOT-SP 10865
(SEVENTH REVISION)

EXPIRATION DATE: 2021-09-30

(FOR RENEWAL, SEE 49 CFR § 107.109)

1. GRANTEE: Robert Gas Cylinder Company, Inc.
San Juan, Puerto Rico
2. PURPOSE AND LIMITATIONS:
 - a. This special permit authorizes the rebuilding and selling of DOT Specification 4B, 4BA and 4BW cylinders in accordance with the procedures prescribed within this special permit, for use in the transportation of hazardous materials authorized in paragraph 6. This special permit provides no relief from the Hazardous Materials Regulations (HMR) other than as specifically stated herein. The most recent revision supersedes all previous revisions.
 - b. The safety analyses performed in development of this special permit only considered the hazards and risks associated with transportation in commerce.
 - c. No party status will be granted to this special permit.
3. REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-180.
4. REGULATIONS FROM WHICH EXEMPTED: 49 CFR § 180.211(a) except as specified herein.
5. BASIS: This special permit is based on the application of Robert Gas Cylinder Company, Inc. dated October 26, 2017, submitted in accordance with § 107.109.

November 03, 2017

6. HAZARDOUS MATERIALS (49 CFR § 172.101):

Hazardous Materials Description			
Proper shipping name	Hazard Class/ Division	Identification Number	Packing Group
Compressed gases, flammable liquids, corrosive materials and other hazardous material that are authorized to be shipped in DOT 4B, 4BA, and 4BW cylinders of 49 CFR Part 173.	As appropriate	As appropriate	As appropriate

7. SAFETY CONTROL MEASURES:

This special permit authorizes the rebuilding and selling of low-pressure, DOT Specification 4B, 4BA and 4BW steel cylinders having water capacities not exceeding 1000 pounds, in accordance with the following:

- a. Only cylinders originally manufactured to a DOT Specification 4B, 4BA and 4BW may be rebuilt and represented as DOT 4B, 4BA or 4BW cylinders.
- b. Rebuilding work must be performed in accordance with the approved Procedures Manual on file in the Office of Hazardous Materials Safety Approvals and Permits Division and § 180.211(a).
- c. Rebuilder must be considered a manufacturer subject to the requirements of § 178.2(a)(2) and Subpart C of Part 178.
- d. After removal of a non-pressure component and before replacement of any non-pressure component, the cylinder must be visually inspected in accordance with the requirements of CGA Pamphlet C-6. Rejected cylinders must be repaired and rebuilt as prescribed in § 180.211 or condemned.
- e. Rebuilding of any cylinder involving a joint subject to internal pressure may only be performed by fusion welding. The rebuilder may rebuild a DOT 4B, 4BA or 4BW cylinder having a water capacity of 20 pounds or greater by replacing a head of the cylinder using a circumferential joint.

November 03, 2017

When this weld joint is located at other than an original welded joint, a notation of this modification must be shown on the Manufacturer's Report of Rebuilding (see Appendix A). Weld joint must be on the cylindrical section of the cylinder.

f. Welding must be:

- (1) Performed in accordance with the procedures and qualification requirements of CGA Pamphlet C-3.
- (2) Performed using welding rods compatible with the material of the cylinder including any non-pressure component.
- (3) Performed on an area free of any contaminant.

g. Any rebuilt cylinder must be:

- (1) Heat treated as required in the applicable specification.
- (2) Subjected to a full hydrostatic volumetric expansion test on each cylinder as specified in the applicable cylinder specification in Part 178. The results of the tests must conform to the requirements of the applicable cylinder specification.
- (3) Inspected and have test data reviewed to determine conformance with the applicable cylinder specification.
- (4) Made of material in conformance with the specification. Rebuilt cylinders are to be grouped into lots as required in the original specification and heat treated as noted in paragraph (1) above. Each new lot of cylinders must include chemical analysis, verification, inspection and tensile testing of only the replaced part and weldments required to affect the rebuilding. Components used in the original manufacture are accepted as meeting the requirements of the specification subject to acceptable performance of the full expansion test required in paragraph (2).

h. A record of rebuilding must be completed for each cylinder rebuilt in the format presented in Attachment 1 of this special permit.

i. A copy of the reports of rebuilding must be maintained by the rebuilding facility for 15 years.

November 03, 20178. SPECIAL PROVISIONS:

a. Each packaging rebuilt under the authority of this special permit and in accordance with an approval issued under § 180.211(a), must be marked with the approval number issued to the grantee of this special permit.

b. A current copy of this special permit, in addition to the referenced approval document in 8.a., must be maintained at the facility where the cylinders are rebuilt and must be made available to the DOT representative upon request.

9. MODES OF TRANSPORTATION AUTHORIZED: Motor vehicle, rail freight, cargo vessel, cargo aircraft only, and passenger aircraft.

10. MODAL REQUIREMENTS: A current copy of this special permit must be carried aboard each cargo vessel or aircraft used to transport packages covered by this special permit. The shipper must furnish a current copy of this special permit to the air carrier before or at the time the shipment is tendered.

11. COMPLIANCE: Failure by a person to comply with any of the following may result in suspension or revocation of this special permit and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. 5101 et seq:

- o All terms and conditions prescribed in this special permit and the Hazardous Materials Regulations, Parts 171-180.
- o Persons operating under the terms of this special permit must comply with the security plan requirement in Subpart I of Part 172 of the HMR, when applicable.
- o Registration required by § 107.601 et seq., when applicable.

Each "Hazmat employee", as defined in § 171.8, who performs a function subject to this special permit must receive training on the requirements and conditions of this special permit in addition to the training required by §§ 172.700 through 172.704.

No person may use or apply this special permit, including display of its number, when the special permit has expired or is otherwise no longer in effect.

November 03, 2017

Under Title VII of the Safe, Accountable, Flexible, Efficient Transportation Equity Act: A Legacy for Users (SAFETEA-LU)- 'The Hazardous Materials Safety and Security Reauthorization Act of 2005' (Pub. L. 109-59), 119 Stat. 1144 (August 10, 2005), amended the Federal hazardous materials transportation law by changing the term "exemption" to "special permit" and authorizes a special permit to be granted up to two years for new special permits and up to four years for renewals.

12. REPORTING REQUIREMENTS: Shipments or operations conducted under this special permit are subject to the Hazardous Materials Incident Reporting requirements specified in 49 CFR §§ 171.15 - Immediate notice of certain hazardous materials incidents, and 171.16 - Detailed hazardous materials incident reports. In addition, the grantee(s) of this special permit must notify the Associate Administrator for Hazardous Materials Safety, in writing, of any incident involving a package, shipment or operation conducted under terms of this special permit.

Issued in Washington, D.C.



for William Schoonover
Associate Administrator for Hazardous Materials Safety

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Pipeline and Hazardous Materials Safety Administration, Department of Transportation, Washington, D.C. 20590. Attention: PHH-31.

Copies of this special permit may be obtained by accessing the Hazardous Materials Safety Homepage at http://hazmat.dot.gov/sp_app/special_permits/spec_perm_index.htm Photo reproductions and legible reductions of this special permit are permitted. Any alteration of this special permit is prohibited.

PO: swa/SG

ATTACHMENT 1

Manufacturer's Report of Rebuilding

Cylinder Identification

Manufacturer

_____ Cylinder Specification Number and Service Pressure
 _____ Cylinder Serial Number
 _____ Date of Original Manufacture
 _____ Other Identification Marks

Rebuild Information

Chemical Analysis of Replacement Parts

Parts Being Replaced

_____ Heat Identification
 _____ Steel Manufactured by
 _____ Analysis Performed by

C	P	S	Si	Mn	Ni	Cr	Mo	Cu	Al	Zr
---	---	---	----	----	----	----	----	----	----	----

Record of Physical Test of Replacement Parts

Yield PSI	Tensile PSI	Elongation in _____ inches	Reduction of Area %	Weld Tensile	Weld bend
_____	_____	_____	_____	_____	_____

Record of Hydrostatic Test

Calculated Volumetric Capacity of Cylinder Being Rebuilt

Actual Test Pressure	Total Expansion	Permanent Expansion	% of Total to Perman.	Volumetric Capacity
_____	_____	_____	_____	_____

(Volumetric capacity of rebuilt cylinder must be + or - 3% of the calculated capacity)

I certify that this rebuilt cylinder is accurately represented by the data above and that all provisions of DOT-SP 10865 and other applicable regulations have been complied with.

Repair Technician _____ Date

Company Representative _____ Date