

March 4, 2011



U.S. Department
of Transportation

East Building, PHH-30
1200 New Jersey Avenue S.E.
Washington, D.C. 20590

**Pipeline and Hazardous
Materials Safety Administration**

DOT-SP 12920
(NINTH REVISION)

(FOR RENEWAL, SEE 49 CFR § 107.109)

1. GRANTEE: (See individual authorization letter)
2. PURPOSE AND LIMITATION:
 - a. This special permit authorizes the transportation in commerce of certain pyrophoric materials in a combination package consisting of UN1A2 outer package and a UN1A1 inner package. This special permit provides no relief from the Hazardous Materials Regulations (HMR) other than as specifically stated herein. The most recent revision supersedes all previous revisions.
 - b. The safety analyses performed in development of this special permit only considered the hazards and risks associated with transportation in commerce.
 - c. Unless otherwise stated herein, this special permit consists of the special permit authorization letter issued to the grantee together with this document.
3. REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-180.
4. REGULATIONS FROM WHICH EXEMPTED: 49 CFR § 173.181(c) in that an inner package of greater than 4 liters is not authorized and § 173.181(c)(1) in that an inner packaging must have no opening exceeding 25mm in diameter, except as specified herein.
5. BASIS: This special permit is based on the Pipeline and Hazardous Materials Safety Administration's (PHMSA) editorial review under § 107.121 initiated on December 4, 2008.

6. HAZARDOUS MATERIALS (49 CFR § 172.101):

Hazardous Materials Description			
Proper Shipping Name	Hazard Class/ Division	Identification Number	Packing Group
Aluminum alkyls	4.2	UN3051	I
Diethylzinc	4.2	UN1366	I
Dimethylzinc	4.2	UN1370	I
Organometallic substance, liquid, pyrophoric, water-reactive, n.o.s.	4.2	UN3394	I

7. SAFETY CONTROL MEASURES:

a. PACKAGING - The prescribed packaging system consists of the following:

(1) Outer Packaging - A 208 liter capacity UN1A2 drum which has been certified to PG I. The drum has a minimum wall thickness of 1.0 mm and the top head is closed with a 2.4 mm steel closing ring.

(2) Inner Packaging - A 10 liter or 20 liter UN1A1 drum which have been certified to PG I. The drums have a minimum wall thickness of 1.9 mm. Both drums have 4 NPT or VCR openings, each with a diameter of 6.3 mm. The 10 liter drum is fabricated from 316 stainless steel and the 20 liter drum is fabricated from 304 stainless steel. On the upper head, both the 10 and 20 liter drums are fitted with a center opening with a maximum diameter of 68.3 mm. The opening is sealed with a threaded closure fabricated from 316 stainless steel.

b. OPERATIONAL CONTROLS - No more than two (2) inner drums may be placed inside the outer drum.

8. SPECIAL PROVISIONS:

a. A person who is not a holder of this special permit who receives a package covered by this special permit may reoffer it for transportation provided no modification or change is made to the package or its contents and it is reoffered for transportation in conformance with this special permit and the HMR.

b. A current copy of this special permit must be maintained at each facility where the package is offered or reoffered for transportation.

9. MODES OF TRANSPORTATION AUTHORIZED: Motor vehicle and cargo vessel.10. MODAL REQUIREMENTS: A current copy of this special permit must be carried aboard each cargo vessel, or motor vehicle used to transport packages covered by this special permit.11. COMPLIANCE: Failure by a person to comply with any of the following may result in suspension or revocation of this special permit and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. 5101 et seq.

- o All terms and conditions prescribed in this special permit and the Hazardous Materials Regulations, 49 CFR Parts 171-180.
- o Persons operating under the terms of this special permit must comply with the security plan requirement in Subpart I of Part 172 of the HMR, when applicable.
- o Registration required by § 107.601 et seq., when applicable.

Each "Hazmat employee", as defined in § 171.8, who performs a function subject to this special permit must receive training on the requirements and conditions of this special permit in addition to the training required by §§ 172.700 through 172.704.

No person may use or apply this special permit, including display of its number, when this special permit has expired or is otherwise no longer in effect.

March 4, 2011

Under Title VII of the Safe, Accountable, Flexible, Efficient Transportation Equity Act: A Legacy for Users (SAFETEA-LU) - 'The Hazardous Materials Safety and Security Reauthorization Act of 2005' (Pub. L. 109-59), 119 Stat. 1144 (August 10, 2005), amended the Federal hazardous materials transportation law by changing the term "exemption" to "special permit" and authorizes a special permit to be granted up to two years for new special permits and up to four years for renewals.

12. REPORTING REQUIREMENTS: Shipments or operations conducted under this special permit are subject to the Hazardous Materials Incident Reporting requirements specified in 49 CFR §§ 171.15 Immediate notices of certain hazardous materials incidents, and 171.16 detailed hazardous materials incident reports. In addition, the grantee(s) of this special permit must notify the Associate Administrator for Hazardous Materials Safety, in writing, of any incident involving a package, shipment or operation conducted under terms of this special permit.

Issued in Washington, D.C.:



for Dr. Magdy El-Sibaie
Associate Administrator for Hazardous Materials Safety

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Pipeline and Hazardous Materials Safety Administration, Department of Transportation, Washington, D.C. 20590. Attention: PHH-31.

Copies of this special permit may be obtained by accessing the Hazardous Materials Safety Homepage at http://hazmat.dot.gov/sp_app/special_permits/spec_perm_index.htm Photo reproductions and legible reductions of this special permit are permitted. Any alteration of this special permit is prohibited.

PO: DB/AM