



U.S. Department
of Transportation

**Pipeline and Hazardous
Materials Safety
Administration**

December 06, 2021

1200 New Jersey Avenue, SE
Washington, DC 20590

DOT-SP 14661
(TENTH REVISION)

EXPIRATION DATE: 2025-09-30

(FOR RENEWAL, SEE 49 CFR § 107.109)

1. GRANTEE: FIBA Technologies, Inc.
Littleton, MA
2. PURPOSE AND LIMITATION:
 - a. This special permit authorizes the transportation in commerce of certain Division 2.1 and 2.2 materials in DOT Specification 3A, 3AA, 3AX, 3AAX and 3T cylinders and non-DOT cylinders manufactured under DOT-SP 13230 and DOT-SP 13258 having a water capacity over 125 lbs. that are periodically requalified every ten years rather than every five years. This special permit provides no relief from the Hazardous Materials Regulations (HMR) other than as specifically stated herein. The most recent revision supersedes all previous revisions.
 - b. The safety analyses performed in development of this special permit only considered the hazards and risks associated with transportation in commerce. The safety analyses did not consider the hazards and risks associated with consumer use, use as a component of a transport vehicle or other device, or other uses not associated with transportation in commerce.
 - c. No party status will be granted to this special permit.
3. REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-180.
4. REGULATIONS FROM WHICH EXEMPTED: 49 CFR §§ 180.209(a) and 180.209(b)(1), in that cylinders with water capacity over 125 lbs. may be requalified every ten years and they are not required to be removed from bundles and hammer tested prior to each refill; and § 180.209(b)(1)(iv) in that acoustic emission and ultrasonic examination (AE/UE) is authorized in lieu of hydrostatic testing and visual inspection.

NOTE: This does not relieve the holder of this special permit from securing an approval for retesting cylinders from the Associate Administrator for Hazardous Materials Safety.

5. BASIS: This special permit is based on the application of FIBA Technologies, Inc. dated October 15, 2021, submitted in accordance with § 107.109.
6. HAZARDOUS MATERIALS (49 CFR § 172.101):

Hazardous Materials Description			
Proper Shipping Name	Hazard Class/ Division	Identification Number	Packing Group
1,1-Difluoroethylene <i>or</i> Refrigerant gas R 1132a	2.1	UN1959	N/A
1-Chloro-1,1-difluoroethane <i>or</i> Refrigerant gas R 142b	2.1	UN2517	N/A
Air, compressed	2.2	UN1002	N/A
Argon, <i>compressed</i>	2.2	UN1006	N/A
Chlorodifluoromethane <i>or</i> Refrigerant gas R 22	2.2	UN1018	N/A
Chlorinated hydrocarbons, fluorinated hydrocarbons or liquefied hydrocarbons	2.1, 2.2	Various	N/A
Cyclopropane	2.1	UN1027	N/A
Ethylene	2.1	UN1962	N/A
Helium, compressed	2.2	UN1046	N/A
Hexafluoroethane, compressed <i>or</i> Refrigerant gas R 116	2.2	UN2193	N/A
Hydrogen, compressed	2.1	UN1049	N/A
Krypton, compressed	2.2	UN1056	N/A
Mixtures of air, argon, cyclopropane, ethylene, helium, hydrogen, krypton, neon, nitrogen, nitrous oxide, oxygen, sulfur hexafluoride, and xenon that are commercially free from corroding components and have a dew point at or below minus 52 °F at 1 atmosphere	2.1, 2.2	Various	N/A

Hazardous Materials Description			
Proper Shipping Name	Hazard Class/ Division	Identification Number	Packing Group
Neon, compressed	2.2	UN1065	N/A
Nitrogen trifluoride	2.2	UN2451	N/A
Nitrogen, compressed	2.2	UN1066	N/A
Nitrous oxide	2.2	UN1070	N/A
Oxygen, compressed	2.2	UN1072	N/A
Silane	2.1	UN2203	N/A
Sulfur hexafluoride	2.2	UN1080	N/A
Tetrafluoromethane, compressed <i>or</i> Refrigerant gas R 14	2.2	UN1982	N/A
Trifluoromethane <i>or</i> Refrigerant gas R 23	2.2	UN1984	N/A
Compressed gas, n.o.s. (mixture of Air, Argon, R22, Helium, R116, Neon, Nitrogen trifluoride, Nitrogen, Nitrous oxide, Oxygen, Sulfur hexafluoride, R14, and/or R23)	2.2	UN1956	N/A
Compressed gas, flammable, n.o.s. (mixture of R 1132a, R142b, Air, Argon, R22, Ethylene, Helium, R116, Hydrogen, Neon, Nitrogen trifluoride, Nitrogen, Nitrous oxide, Oxygen, Silane, Sulfur hexafluoride, R14, and/or R23)	2.1	UN1954	N/A
Methane, compressed or Natural gas, compressed (with high methane content) *	2.1	UN1971	N/A
Xenon, compressed	2.2	UN2036	N/A

* This material must meet the requirements of §173.302a(a)(4)

7. SAFETY CONTROL MEASURES:

- a. PACKAGING: Packaging prescribed are DOT 3A, 3AA, 3AX, 3AAX and 3T cylinders (tubes) and non-DOT cylinders manufactured under DOT-SP 13230 and

DOT-SP 13258, that are subjected to periodic requalification and marking specified in §§ 180.205, 180.209, and 180.213 except that:

- (1) Each tube must be retested at least once every 10 years by utilizing the acoustic emission and ultrasonic examination (AE/UE) procedures specified in DOT-SP 9847 (FIBA Technologies, Inc.) except the maximum acceptance flaw size is 10% of the minimum design wall thickness of the cylinder (tube). The 10-year requalification period applies only to cylinders that meet all requirements specified in § 180.209(b) except that the cylinders may have a water capacity over 125 lbs and they are not hammer tested.
- (2) Tubes with an outside diameter (OD) less than 18 inches must be mounted with adequate spacing between each tube. The minimum required vertical spacing between each tube must be such that it will allow UE follow-up transducer assembly (wedge) scans of the OD of all tubes in 90° quadrants.
- (3) Every five years, each cylinder/tube including the cylinder neck and flange/sleeve area must be subjected to an external visual inspection (without disassembly) in accordance with CGA Pamphlet C-6 by a valid Requalification Identification Number (RIN) holder. A tube with excessive corrosion around the neck or under the flange/sleeve must be removed and examined further in accordance with CGA Pamphlet C-23. The results of the visual inspection must be recorded for each cylinder/tube and the report submitted to the Office of Hazardous Materials Safety Approvals and Permits Division (OHMSAPD) upon request. The RIN holder performing the 5-year visual inspection must mark their RIN number and the month and year of inspection on the packaging.

b. OPERATIONAL CONTROLS:

- (1) This special permit is limited to the DOT specification cylinders and non-DOT specification cylinders manufactured under DOT-SP 13230 and DOT-SP 13258 described in paragraph 7.a. above. Flat bottom cylinders are not covered by this special permit.
- (2) Prior to use, the external neck threads and flange/sleeve of each tube with a diameter greater than or equal to 18" and mounted on tube trailers or modules must be inspected in accordance with CGA Pamphlet C-23. This inspection must be periodically repeated at least once every ten years.
- (3) Each DOT 3T cylinder and non-DOT cylinder manufactured under DOT-SP 13258, must be subjected to shear wave ultrasonic examination (UE). The UE must be performed by an authorized DOT UE special permit holder or the cylinder (tube) manufacturer. The maximum acceptance defect (pitting corrosion, crack) for a tube that is tested by UE shear wave is 5% of the minimum design wall thickness of the tube. The UE shear wave must cover 100% of the sidewall of the cylinder.

- (4) Maximum cycling (number of fillings) in a 10-year period must be less than or equal to 600 for DOT 3A, 3AA, 3AX, 3AAX and non-DOT cylinders manufactured under SP 13230 and 300 for DOT 3T cylinders and non-DOT cylinders manufactured DOT-SP 13258. FIBA Technologies, Inc. must record all fillings of each cylinder and submit the report to OHMSAPD upon request.
- (5) The maximum acceptance flaw size for the DOT 3T specification cylinder and non-DOT cylinder manufactured under DOT-SP 13258 used for silane service and requalified under this special permit using AE/UE must be 10% of the minimum design wall thickness of the cylinder (tube).
- (6) All gases and gas mixture must have a dew point at or below minus 52 °F at one atmosphere.
- (7) Carbon dioxide or corrosive gas in any concentration cannot be added to these cylinders.
- (8) Hydrogen or hydrogen bearing gases are not authorized in DOT Specification 3T cylinders and non-DOT cylinders manufactured under DOT-SP 13258.
- (9) No person may perform requalification of cylinders/tubes subject to this special permit using UE or AE/UE unless:
 - (i) That person is an employee of FIBA Technologies, Inc. and has a current copy of this special permit at the location of such requalification; and
 - (ii) Complies with all the terms and conditions of this special permit.

8. SPECIAL PROVISIONS:

- a. A person who is not a holder of this special permit who receives a package covered by this special permit may reoffer it for transportation provided no modifications or changes are made to the package and it is reoffered for transportation in conformance with this special permit and the HMR.
- b. Shippers (offerors) may use the cylinders specified and tested in accordance with the provisions of this special permit for the transportation in commerce of those hazardous materials specified herein, provided no modifications or changes are made to the cylinders. All terms of this special permit and other applicable requirements contained in 49 CFR Parts 100-185 must be met.
- c. A current copy of this special permit must be maintained at each facility where the package is offered or reoffered for transportation.

d. MARKING:

- (1) An exterior tube on each side of the bundle or the ISO frame must be marked with letters and numbers at least 2 inches high on a contrasting background "DOT-SP 14661".
- (2) The current retest date must be marked on the rear or side of the frame or the tube trailer at approximately eye level. In the event retest dates of cylinders differ in the frame or the tube trailer, the oldest retest date (meaning the date of the retest that must occur first) will be displayed.
- (3) Each cylinder shipped individually (DOT-3AA ton cylinder or non-DOT cylinder manufactured under DOT-SP 13230) must be plainly and durably marked "DOT-SP 14661" near the existing DOT markings.

e. Transportation of Division 2.1 (flammable gases) hazardous materials is not authorized aboard a cargo vessel unless specifically authorized in the Hazardous Materials Table (§ 172.101).

9. MODES OF TRANSPORTATION AUTHORIZED: Motor vehicle, cargo vessel and rail freight.
10. MODAL REQUIREMENTS: A current copy of this special permit must be carried aboard each cargo vessel or motor vehicle used to transport packages covered by this special permit.
11. COMPLIANCE: Failure by a person to comply with any of the following may result in suspension or revocation of this special permit and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. 5101 et seq.:
 - o All terms and conditions prescribed in this special permit and the Hazardous Materials Regulations, 49 CFR Parts 171-180.
 - o Persons operating under the terms of this special permit must comply with the security plan requirement in Subpart I of Part 172 of the HMR, when applicable.
 - o Registration required by § 107.601 et seq., when applicable.

Each "Hazmat employee", as defined in § 171.8, who performs a function subject to this special permit must receive training on the requirements and conditions of this special permit in addition to the training required by §§ 172.700 through 172.704.

No person may use or apply this special permit, including display of its number, when this special permit has expired or is otherwise no longer in effect.

Under Title VII of the Safe, Accountable, Flexible, Efficient Transportation Equity Act: A Legacy for Users (SAFETEA-LU)— “The Hazardous Materials Safety and Security Reauthorization Act of 2005” (Pub. L. 109-59), 119 Stat. 1144 (August 10, 2005), amended the Federal hazardous materials transportation law by changing the term “exemption” to “special permit” and authorizes a special permit to be granted up to two years for new special permits and up to four years for renewals.

12. **REPORTING REQUIREMENTS:** Shipments or operations conducted under this special permit are subject to the Hazardous Materials Incident Reporting requirements specified in 49 CFR §§ 171.15 Immediate notice of certain hazardous materials incidents, and 171.16 Detailed hazardous materials incident reports. In addition, the grantee(s) of this special permit must notify the Associate Administrator for Hazardous Materials Safety, in writing, of any incident involving a package, shipment or operation conducted under terms of this special permit.

Issued in Washington, D.C.:



for William Schoonover
Associate Administrator for Hazardous Materials Safety

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Pipeline and Hazardous Material Safety Administration, U.S. Department of Transportation, East Building PHH-30, 1200 New Jersey Avenue, Southeast, Washington, D.C. 20590.

Copies of this special permit may be obtained by accessing the Hazardous Materials Safety Homepage at <https://www.phmsa.dot.gov/approvals-and-permits/hazmat/special-permits-search>. Photo reproductions and legible reductions of this special permit are permitted. Any alteration of this special permit is prohibited.

PO: Shafkey/kah