

April 27, 2020



U.S. Department
of Transportation

East Building, PHH-30
1200 New Jersey Avenue S.E.
Washington, D.C. 20590

**Pipeline and Hazardous
Materials Safety Administration**

DOT-SP 20381
(SECOND REVISION)

(FOR RENEWAL, SEE 49 CFR § 107.109)

1. GRANTEE: (See individual authorization letter)
2. PURPOSE AND LIMITATION:
 - a. This special permit authorizes the transportation in commerce of gaseous, solvent free, acetylene in certain DOT and UN specification cylinders. This special permit provides no relief from the Hazardous Materials Regulations (HMR) other than as specifically stated herein. The most recent revision supersedes all previous revisions.
 - b. The safety analyses performed in the development of this special permit only considered the hazards and risks associated with the transportation in commerce.
 - c. Unless otherwise stated herein, this special permit consists of the special permit authorization letter issued to the grantee together with this document.
3. REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-180.
4. REGULATIONS FROM WHICH EXEMPTED: 49 CFR § 172.101 Hazardous Materials Table Column (3) in that the material is forbidden, except as specified herein.
5. BASIS: This special permit is based on the application of Western International Gas & Cylinders, Inc. dated August 22, 2018, submitted in accordance with § 107.109 and additional information dated April 23, 2020.

6. HAZARDOUS MATERIALS (49 CFR 172.101):

Hazardous Materials Description			
Proper Shipping Name	Hazard Class/ Division	Identification Number	Packing Group
Acetylene, solvent free	2.1	UN3374	N/A

7. SAFETY CONTROL MEASURES:a. PACKAGING:

(1) Prescribed packaging shall be a DOT specification 3A, 3AA, or 3AL cylinder with a minimum service pressure rating of 1800 psig (3,000 psig test pressure) or a UN ISO 9809-1, UN ISO 9809-2, UN ISO 9809-3, UN ISO 9809-4, or UN ISO 7866 cylinder with a minimum test pressure rating of 207 bar;

(2) The cylinder shall not exceed a water capacity of 150 pounds (4,160 cubic inches); and

(3) The length of the cylinder shall not exceed 60 inches.

b. OPERATIONAL CONTROLS:

(1) The acetylene pressure in the cylinder corrected to 60 °F shall not exceed 25.5 psig/40 psia;

(2) If the cylinder pressure is filled to pressures above 15 psig, a flash arrestor approved for acetylene must be installed between the cylinder and the filling apparatus;

(3) Cylinders must have three protective features to prevent leakage: a plug in the cylinder outlet, a positive means of securing the valve from turning (i.e., shrink wrap, tie down, etc), and a protective cap over the valve assembly; and

April 27, 2020

(4) A cylinder that has been exposed to decomposition of acetylene resulting in pressures exceeding the marked service pressure (for DOT specification cylinders) or 5/3 of the marked test pressure (for UN ISO cylinders) must be removed from service.

- c. MARKING: The cylinder must be marked "DOT-SP 20381" in addition to the DOT or ISO specification marking.

8. SPECIAL PROVISIONS:

a. A person who is not a holder of this special permit who receives a package covered by this special permit may reoffer it for transportation provided no modification or change is made to the package and it is reoffered for transportation in conformance with this special permit and the HMR.

b. A current copy of this special permit must be maintained at each facility where the package is offered or reoffered for transportation.

9. MODES OF TRANSPORTATION AUTHORIZED: Motor vehicle.

10. MODAL REQUIREMENTS: A current copy of this special permit must be carried aboard each motor vehicle used to transport packages covered by this special permit.

11. COMPLIANCE: Failure by a person to comply with any of the following may result in suspension or revocation of this special permit and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. 5101 et seq:

- o All terms and conditions prescribed in this special permit and the Hazardous Materials Regulations, 49 CFR Parts 171-180.
- o Persons operating under the terms of this special permit must comply with the security plan requirement in Subpart I of Part 172 of the HMR, when applicable.
- o Registration required by § 107.601 et seq., when applicable.

April 27, 2020

Each "Hazmat employee", as defined in § 171.8, who performs a function subject to this special permit must receive training on the requirements and conditions of this special permit in addition to the training required by §§ 172.700 through 172.704.

No person may use or apply this special permit, including display of its number, when this special permit has expired or is otherwise no longer in effect.

Under Title VII of the Safe, Accountable, Flexible, Efficient Transportation Equity Act: A Legacy for Users (SAFETEA-LU)—"The Hazardous Materials Safety and Security Reauthorization Act of 2005" (Pub. L. 109-59), 119 Stat. 1144 (August 10, 2005), amended the Federal hazardous materials transportation law by changing the term "exemption" to "special permit" and authorizes a special permit to be granted up to two years for new special permits and up to four years for renewals.

12. REPORTING REQUIREMENTS: Shipments or operations conducted under this special permit are subject to the Hazardous Materials Incident Reporting requirements specified in 49 CFR §§ 171.15 - Immediate notice of certain hazardous materials incidents, and 171.16 - Detailed hazardous materials incident reports. In addition, the grantee(s) of this special permit must notify the Associate Administrator for Hazardous Materials Safety, in writing, of any incident involving a package, shipment or operation conducted under terms of this special permit.

Issued in Washington, D.C.:



for William Schoonover
Associate Administrator for Hazardous Materials Safety

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Pipeline and Hazardous Material Safety Administration, U.S. Department of Transportation, East Building PHH-30, 1200 New Jersey Avenue, Southeast, Washington, D.C. 20590.

April 27, 2020

Copies of this special permit may be obtained by accessing the Hazardous Materials Safety Homepage at http://hazmat.dot.gov/sp_app/special_permits/spec_perm_index.htm. Photo reproductions and legible reductions of this special permit are permitted. Any alteration of this special permit is prohibited.

PO: rt/NICKS