



U.S. Department
of Transportation

Research and
Special Programs
Administration

400 Seventh Street, S.W.
Washington, D.C. 20590

DOT-E 8549 (EXTENSION)
SECOND REVISION August 5, 1987

In accordance with 49 CFR 107.105 of the Department of Transportation (DOT) Hazardous Materials Regulations DOT-E 8549 is hereby extended for the party(ies) listed below by changing the expiration date in paragraph 10 to August 31, 1993. This change is effective from the issue date of this extension. All other terms of the exemption remain unchanged.

This extension applies only to party(ies) listed below based on the application(s) received in accordance with 49 CFR 107.105. This extension constitutes a necessary part of this exemption and must be attached to it.

Alan I. Roberts
Alan I. Roberts
Associate Administrator
for Hazardous Materials Safety

FEB 26 1993

(DATE)

Dist: FHWA

EXEMPTION HOLDER

APPLICATION DATE

United Pumping Service, Inc.
City of Industry, CA

December 1, 1992



US Department
of Transportation

Research and
Special Programs
Administration

400 Seventh Street S.W.
Washington D.C. 20590

DOT-E 8549
(SECOND REVISION)

AUG 5 1987

1. United Pumping Service, Inc., (UPSI), City of Industry, Ca., is hereby granted an exemption from those provisions of this Department's Hazardous Materials Regulations specified in paragraph 5 below to offer packages as described in paragraph 7 below for use in the transportation of the hazardous materials described in paragraph 3 below in commerce subject to the requirements specified herein. This exemption authorizes use of a non-DOT specification cargo tank, and provides no relief from any regulation other than specifically stated.

2. BASIS. This exemption is based on Peters Manufacturing Company's application dated December 22, 1980, and the petitions for reconsideration dated November 11, 1981 and January 15, 1982, and UPSI's application dated June 29, 1987, submitted in accordance with 49 CFR 107.103, and 49 CFR 107.105, respectively, and the public proceeding thereon.

3. HAZARDOUS MATERIALS (Descriptor and class). Liquid and semi-solid waste material, including mixtures, compatible with the packaging, containing flammable liquids or corrosives or poison B materials, or combinations thereof, classed as flammable liquid, corrosive material or poison B as appropriate.

4. PROPER SHIPPING NAME (49 CFR 172.101). Specific commodity name, or generic description, as appropriate.

5. REGULATION AFFECTED. 49 CFR 173.119(a) and (m), 173.245(a), 173.346(a), 178.340-7, 178.342-5, 178.343-5.

6. MODES OF TRANSPORTATION AUTHORIZED. Motor vehicle.

7. SAFETY CONTROL MEASURES. Packaging prescribed is a non-DOT specification cargo tank designed and constructed in full compliance with DOT Specification MC-307 or MC-312 (49 CFR 178.340, 178.342, 178.343) except as follows:

a. The cargo tank must be designed, built and certified in accordance with Section VIII of the ASME Code to a minimum design pressure as follows:

Basic Cargo Tank Specification	Design Pressure (psig)		Minimum Test Pressure (psig)
	Internal (See Note 1)	External (See Note 2)	
MC 307	25	15	37.5
MC 312	25	15	37.5

Note 1: The design pressure must be at least equal to the maximum pressure used for unloading.

Note 2: Vacuum tanks must have an external design pressure of at least 15 psi.

b. Circumferential reinforcement must comply with 49 CFR 178.340-7 except the maximum unreinforced portion of the shell may exceed 60-inches provided thickness and tensile strength of the shell material in combination with the frame and circumferential reinforcement produces structural integrity at least equal to that prescribed in 49 CFR 178.340-4(b).

c. In place of internal valves prescribed in 49 CFR 178.342-5(a) and 178.343-5(b), each tank may be equipped with one 6-inch maximum diameter bottom outlet with remote closure with self closing gate, plug or butterfly valve and one optional 4-inch maximum diameter bottom inlet with gate, plug or butterfly valve located near the rear of tank in accordance with sketches and photographs submitted with the application on file with the Office of Hazardous Materials Transportation (OHMT). Each bottom outlet and each bottom inlet must be equipped with an additional shut-off valve, or a blank flange or a sealing cap.

d. The metal identification plate and the manufacturer's certificate must not be marked to indicate compliance with DOT MC-307 or MC-312 specifications but instead must bear reference to DOT-E 8549.

e. Tanks that are to be used in transporting flammable waste materials must be equipped with a spring loaded relief valve.

8. SPECIAL PROVISIONS.

a. A copy of this exemption must be carried aboard each motor vehicle used to transport packages covered by this exemption.

b. Each cargo tank must be reinspected and retested once every two years in accordance with 49 CFR 177.824 as prescribed for DOT Specification MC-307 or MC 312 cargo tanks, as appropriate, at one and one-half times the design pressure.

c. Each cargo tank must be plainly marked on the right side near the front, in letters at least two inches high on a contrasting background, "DOT-E 8549."

d. The Manufacturer's Data Report for the first cargo tank fabricated must be submitted to the OHMT prior to initial shipment.

e. Twelve stainless steel cargo tanks built in compliance with Peter Manufacturing Company's specification on file with the OHMT may be used under the terms of this exemption. No new construction is authorized. These cargo tanks must have been built before December 15, 1981 and bear serial numbers 1011, 1040, 1050, 1055, 1060, 1065, 1070, 1075, 1085, 1095, 2005 and 2015.

9. REPORTING REQUIREMENTS. Any incident involving loss of contents of the package or cargo tank rollover must be reported to the OHMT as soon as practicable.

10. EXPIRATION DATE. July 15, 1989.

Issued at Washington, D.C.:

SA *A. Suzanne Hedges*
Alan I. Roberts
Director
Office of Hazardous Materials Transportation

AUG 5 1987

(DATE)

Address all inquiries to: Director, Office of Hazardous Materials Transportation, Research and Special Programs Administration, U.S. Department of Transportation, Washington, D.C. 20590. Attention: Exemptions Branch.

Dist: FHWA.