

GENERAL INSTRUCTIONS

Each operator of a hazardous liquid pipeline system shall file Form PHMSA F 7000-1 for an accident that meets the criteria in 49 CFR §195.50 as soon as practicable but not more than 30 days after discovery of the accident. Requirements for submitting reports are in §195.54 and §195.58.

Hazardous liquid releases during maintenance activities are not to be reported if the spill was less than 5 barrels, not otherwise reportable under 49 CFR §195.50, did not result in water pollution as described by 49 CFR §195.52(a)(4), was confined to company property or pipeline right-of-way, and was cleaned up promptly. Any spill of 5 gallons or more to water shall be reported.

Special considerations apply when a pipeline failure or release occurs involving secondary ignition. Secondary ignition is a fire where the origin of the fire is unrelated to the pipelines systems subject to Part 195, such as electrical fires, arson, etc., and includes events where fire or explosion not originating from a pipeline system failure or release was the primary *cause* of the pipeline system failure or release, such as a refinery fire that subsequently resulted in – but was not caused by – a hazardous liquid pipeline system failure or release. An accident caused by secondary ignition is not to be reported unless a release of hazardous liquid escaping from facilities subject to regulation under Part 195 results in one or more of the consequences as described in §195.50. The determination of consequences from a pipeline accident caused by secondary ignition, though, is an area of possible confusion when reporting accidents. This situation is particularly susceptible to confusion as compared to other Natural or Other Outside Force Damage because it is extremely difficult in most cases to establish whether and which consequences were attributable to the initiating fire (that is, the “secondary ignition” source itself) or to a subsequent fire due to a resulting pipeline system failure or release. PHMSA is providing the following guidance for operators to use when secondary ignition is involved (sometimes referred to as “Fire First” accidents):

- A pipeline accident attributed to secondary ignition is to be reported to PHMSA if any fatalities or injuries are involved unless it can be established with reasonable certainty that all of the casualties either preceded the pipeline system failure or release, or would have occurred whether or not the pipeline system failure or release occurred.
- A pipeline accident attributed to secondary ignition is NOT to be reported to PHMSA unless the damage to facilities subject to Part 195 exceeds \$50,000.

These considerations apply to several pipeline accident cause categories as indicated in pertinent sections of these instructions.

PHMSA requires electronic reporting. Follow these instructions for electronic filing or to request an alternative reporting method. If you have questions about this report or these instructions, contact PHMSA’s Information Resources Manager at 202-366-8075. If you need copies of Form PHMSA F 7000-1 and/or instructions they can be found on the

INSTRUCTIONS FOR FORM PHMSA F 7000-1 (Rev. 10-2011)
ACCIDENT REPORT – HAZARDOUS LIQUID PIPELINE SYSTEMS

Pipeline Safety Community main page, <http://phmsa.dot.gov/pipeline>, by clicking the Library hyperlink and then selecting the Forms link under the “Mini-Menu” on the right side of the page. The applicable forms are listed in the section titled Accidents/Incidents/Annual Reporting Forms.

195.50 Reporting accidents.

An accident report is required for each failure in a pipeline system subject to this part in which there is a release of the hazardous liquid or carbon dioxide transported resulting in any of the following:

(a) Explosion or fire not intentionally set by the operator.

(b) Release of 5 gallons (19 liters) or more of hazardous liquid or carbon dioxide, except that no report is required for a release of less than 5 barrels (0.8 cubic meters) resulting from a pipeline maintenance activity if the release is:

- (1) Not otherwise reportable under this section;**
- (2) Not one described in §195.52(a)(4);**
- (3) Confined to company property or pipeline right-of-way; and**
- (4) Cleaned up promptly;**

(c) Death of any person;

(d) Personal injury necessitating hospitalization;

(e) Estimated property damage, including cost of clean-up and recovery, value of lost product, and damage to the property of the operator or others, or both, exceeding \$50,000.

195.52 Immediate notice of certain accidents.

(a) Notice requirements. At the earliest practicable moment following discovery of a release of the hazardous liquid or carbon dioxide transported resulting in an event described in §195.50, the operator of the system must give notice, in accordance with paragraph (b) of this section, of any failure that:

- (1) Caused a death or a personal injury requiring hospitalization;**
- (2) Resulted in either a fire or explosion not intentionally set by the operator;**
- (3) Caused estimated property damage, including cost of cleanup and recovery, value of lost product, and damage to the property of the operator or others, or both, exceeding \$50,000;**

(4) Resulted in pollution of any stream, river, lake, reservoir, or other similar body of water that violated applicable water quality standards, caused a discoloration of the surface of the water or adjoining shoreline, or deposited a sludge or emulsion beneath the surface of the water or upon adjoining shorelines; or

(5) In the judgment of the operator was significant even though it did not meet the criteria of any other paragraph of this section.

(b) Information required. Each notice required by paragraph (a) of this section must be made to the National Response Center either by telephone to 800-424-8802 (in Washington, DC, 202-267-2675) or electronically at <http://www.nrc.uscg.mil> and must include the following information:

(1) Name, address and identification number of the operator.

(2) Name and telephone number of the reporter.

(3) The location of the failure.

(4) The time of the failure.

(5) The fatalities and personal injuries, if any.

(6) Initial estimate of amount of product released in accordance with paragraph (c) of this section.

(7) All other significant facts known by the operator that are relevant to the cause of the failure or extent of the damages.

(c) Calculation. A pipeline operator must have a written procedure to calculate and provide a reasonable initial estimate of the amount of released product.

(d) New information. An operator must provide an additional telephonic report to the NRC if significant new information becomes available during the emergency response phase of a reported event at the earliest practicable moment after such additional information becomes known.

§ 195.54 Accident reports.

(a) Each operator that experiences an accident that is required to be reported under §195.50 must, as soon as practicable, but not later than 30 days after discovery of the accident, file an accident report on DOT Form 7000-1, or a facsimile.

(b) Whenever an operator receives any changes in the information reported or additions to the original report on DOT Form 7000-1, it shall file a supplemental report within 30 days.

Further information regarding when reports are identified as “Final” will be covered below under PART A – Key Report Information.

INSTRUCTIONS FOR FORM PHMSA F 7000-1 (Rev. 10-2011)
ACCIDENT REPORT – HAZARDOUS LIQUID PIPELINE SYSTEMS

ONLINE REPORTING REQUIREMENTS

Accident Reports must be submitted online unless an alternate method is approved (see Alternate Reporting Methods below).

The following two separate PIN/Password requirements must be fulfilled prior to submitting data online:

1. You must have a PHMSA-provided Operator Identification Number (OPID) and Personal Identification Number (PIN). If you do not have one, complete and submit the form located on the PHMSA-Office of Pipeline Safety Online Data Entry and Operator Registration System New Operator Registration web site at <http://opsweb.phmsa.dot.gov> to obtain one.
2. You must ALSO have a Username and Password obtained by registering through the PHMSA Portal. If you have a PHMSA OPID and PIN, you may obtain a Username and Password through the PHMSA Portal. If you do not have a Username and Password for the PHMSA Portal, go to <https://portal.phmsa.dot.gov/pipeline> and click on *Create Account* and complete the form as required.

Important: Each operator without an OPID is to plan accordingly and allow for several weeks prior to the due date of the Report to obtain their OPID from PHMSA.

REPORTING METHODS

Accident Reports must be submitted online unless an alternate method is approved (see Alternate Reporting Methods below). Use the following procedure for online reporting:

1. Navigate to the **Online Data Entry System (ODES 2.0)** at the following URL <http://pipelineonlinereporting.phmsa.dot.gov/>.
2. Enter Operator Identification Number (OPID) and PIN. *Note: The operator name that appears is assigned to the OPID and PIN, and is automatically populated by our database and cannot be changed by the operator at the time of filing.*
3. Under “**Create Reports**” on the left side of the screen, select “Hazardous Liquid Accident Report” and proceed with entering your data. *Note: Data fields marked with a single asterisk are considered required fields that must be completed before the system will accept your initial submission.*
4. Click “**Submit**” when finished with your data entry to have your report uploaded to PHMSA’s database as an official submission of an Accident Report; or click “**Save**” which doesn’t submit the report to PHMSA but stores it in a draft status to allow you to come back to complete your data entry and report submission at a later time. *Note: The “Save” feature will allow you to start a report and save a draft of it which you can print out and/or save as a PDF to email to colleagues in order to*

INSTRUCTIONS FOR FORM PHMSA F 7000-1 (Rev. 10-2011)
ACCIDENT REPORT – HAZARDOUS LIQUID PIPELINE SYSTEMS

gather additional information and then come back to accurately complete your data entry before submitting it to PHMSA.

5. Once you click “**Submit**”, the system will return you to the initial view of the screen that lists your [Saved Incident/Accident Reports] in the top portion of the screen and your [Submitted Incident/Accident Reports] in the bottom portion of the screen. *Note: To confirm that your report was successfully submitted to PHMSA, look for it in the bottom portion of the screen where you can also view a PDF of what you submitted.*

Supplemental Report Filing – Follow Steps 1 and 2 above, and then select a previously submitted report from the [Submitted Incident/Accident Reports] list in the bottom portion of the screen by double clicking on the desired report. The report will default to a “Read Only” mode that is pre-populated with the data you entered previously. To create a Supplemental Report, click on “Create Supplemental” found in the upper right corner of the screen. At this point, you can amend your data and make an official submission of the report to PHMSA as either a Supplemental Report or as a Supplemental Report *plus* Final Report (see “Specific Instructions, PART A, Report Type”), or you can use the “**Save**” feature to create a draft of your Supplemental Report to be submitted at some future date. Reports that were saved will appear in the [Saved Incident/Accident Reports] list in the top portion of the screen and reports that were submitted will appear in the [Submitted Incident/Accident Reports] list in the bottom portion of the screen.

If you submit your report online, DO NOT MAIL OR FAX a hardcopy of the completed report to DOT as this may result in duplicate entries.

Alternate Reporting Methods

Operators for whom electronic reporting imposes an undue burden and hardship may submit a written request for an alternate reporting method. Operators must follow the requirements in §195.58(d) to request an alternate reporting method and must comply with any conditions imposed as part of PHMSA’s approval of an alternate reporting method.

RETRACTING A 30-DAY WRITTEN REPORT

An operator who reports an accident in accordance with §195.54 (oftentimes referred to as a 30-day written report) and upon subsequent investigation determines that the event did not meet the criteria in §195.50 may request that the report be retracted. Requests to retract a 30-day written report are to be emailed to InformationResourcesManager@dot.gov. Requests are to include the following information:

- a. The Report ID (the unique 8-digit identifier assigned by PHMSA)
- b. Operator name
- c. PHMSA-issued OPID number

INSTRUCTIONS FOR FORM PHMSA F 7000-1 (Rev. 10-2011)
ACCIDENT REPORT – HAZARDOUS LIQUID PIPELINE SYSTEMS

- d. The number assigned by the National Response Center (NRC) when an immediate notice was made in accordance with §191.5. If Supplemental Reports were made to the NRC for the event, list all NRC report numbers associated with the event.
- e. Date of the event
- f. Location of the event
- g. A brief statement as to why the report should be retracted.

Note: PHMSA no longer requests that operators rescind erroneously reported “Immediate Notices” filed with the NRC in accordance with §195.52 (oftentimes referred to as “Telephonic Reports”).

SPECIAL INSTRUCTIONS

Certain data fields must be completed before an Original Report will be accepted. The data fields that must be completed for an Original Report to be accepted are indicated on the online form. Your Original Report will not be able to be submitted online until the required information has been provided, although your partially completed form can be saved online so that you can return at a later time to provide the missing information.

1. An entry should be made in each applicable space or check box, unless otherwise directed by the section instructions.
2. If the data is unavailable, enter “Unknown” for text fields and leave numeric fields and fields using check boxes or “radio” buttons blank.
3. Estimate data only if necessary. Provide an estimate in lieu of answering a question with “Unknown” or leaving the field blank. Estimates should be based on best-available information and reasonable effort.
4. For unknown or estimated data entries, the operator should file a Supplemental Report when additional information becomes available.
5. If the question is not applicable, please enter “N/A” for text fields and leave numeric fields and fields using check boxes or “radio” buttons blank. Do not enter zero unless this is the actual value being submitted for the data in question.

INSTRUCTIONS FOR FORM PHMSA F 7000-1 (Rev. 10-2011)
ACCIDENT REPORT – HAZARDOUS LIQUID PIPELINE SYSTEMS

6. For questions requiring numeric answers, all preceding and/or unused data fields should be filled in using zeroes. When decimal points or commas are required and not already shown in the data field, **the decimal point or comma should be placed in a separate block** in the data field.

Examples:

(Part C, item 3.a,) Nominal diameter of pipe (in):	<u>/0/0/2/4/</u>	(24 inches)
	<u>/3/./5/</u>	(3.5 inches)
(Part C, item 3.b), Wall thickness (in)	<u>/0/./3/1/2/</u>	(0.312 inches)
(Part C, item 3.c), SMYS	<u>/0/5/2/./0/0/0/</u>	(52,000 psi)

7. If **OTHER** is checked for any answer to a question, include an explanation or description on the line provided, making it clear why “Other” was the necessary selection.
8. Pay close attention to each question for the phrase:
- a. **(select all that apply)**
 - b. **(select only one)**

If the phrase does not exist for a given question, then “select only one” should apply. “Select only one” means that you should select the single, primary, or most applicable answer. **DO NOT SELECT MORE ANSWERS THAN REQUESTED.** “Select all that apply” requires that all applicable answers (one or more than one) be selected.

9. **Date format** = mm/dd/yy or for year = /yyyy/
10. **Time format:** All times are reported as a 24-hour clock:

Time format Examples:

- a. (0000) = midnight = /0/0/0/0/
- b. (0800) = 8:00 a.m. = /0/8/0/0/
- c. (1200) = Noon = /1/2/0/0/
- d. (1715) = 5:15 p.m. = /1/7/1/5/
- e. (2200) = 10:00 p.m. = /2/2/0/0/

Local time always refers to time at the site of the accident. Note that time zones at the accident site may be different than the time zone for the person discovering or reporting the event. For example, if a release occurs at an gas transmission facility in Denver, Colorado at 2:00 pm MST, but an individual located in Houston is filing the report after having been notified at 3:00 pm CST, the time of the accident is to be reported as 1400 hours based on the time in Denver, which is the physical site of the accident.

SPECIFIC INSTRUCTIONS

PART A – GENERAL REPORT INFORMATION

Report Type: (select all that apply)

Select the appropriate report box or boxes to indicate the type of report being filed. Depending on the descriptions below, the following combinations of boxes - and only one of these combinations - may be selected:

- Original Report only
- Original Report *plus* Final Report
- Supplemental Report only
- Supplemental Report *plus* Final Report

☐ **Original Report**

Select this type of report if this is the FIRST report filed for this accident, and not enough information is available at this time to conclude that this is also a Final Report where no further information will be forthcoming. Select Original Report in cases where further information may be forthcoming, such as when final property damage numbers or apparent failure cause is not immediately available).

☐ **Original Report** *plus* ☐ **Final Report**

Select **both** Original Report and Final Report if ALL of the information requested is known and can be provided at the time the initial report is filed, including final property damage costs and apparent failure cause information. Selecting both these types of reports will indicate that further information is not expected to be forthcoming through a Supplemental Report. If, however, for some reason new, updated, and/or corrected information becomes available unexpectedly, the operator is to still file a Supplemental Report indicating such and explaining the circumstances in PART H – Narrative Description of the Accident.

☐ **Supplemental Report**

Select this type of report only if you have already filed an Original Report AND you are now providing new, updated, and/or corrected information. Multiple Supplemental Reports are to be submitted, as necessary, in order to provide new, updated, and/or corrected information **when it becomes available** and, per §191.15(c), each Supplemental Report containing new, updated, and/or corrected information is to be filed as soon as practicable. Submission of new, updated, and/or corrected information is NOT to be delayed in order to accumulate “enough” to “warrant” a Supplemental Report, or to complete a Final Report.

INSTRUCTIONS FOR FORM PHMSA F 7000-1 (Rev. 10-2011)
ACCIDENT REPORT – HAZARDOUS LIQUID PIPELINE SYSTEMS

Supplemental Reports must be filed as soon as practicable following the Operator's awareness of new, updated, and/or corrected information. Failure to comply with these requirements can result in enforcement actions, including the assessment of civil penalties not to exceed \$100,000 for each violation for each day that such violation persists up to a maximum of \$1,000,000.

In cases where an accident results in long-term remediation, an operator may cease filing Supplemental Reports in the following situations and, instead, file a Final Report even when additional remediation costs and recovery of released commodity are still occurring:

1. When the accident response consists only of long-term remediation and/or monitoring which is being conducted under the auspices of an authorized governmental agency or entity.
2. When the estimated final costs and volume of commodity recovered can be predicted with a reasonable degree of certainty.
3. When the volume of commodity recovered over time is consistently decreasing to the point where an estimated total volume of commodity recovered can be predicted with a reasonable degree of accuracy.
4. When the operator can justify (and explain in the Part H – Narrative) that the continuation of Supplemental Report filings in the future will not provide any essential information which will be critically different than that contained in a Final Report filed currently.

In any of these cases, though, if the reported total volume of commodity released or other previously reported data other than “Estimated cost of Operator’s environmental remediation” or “Estimated volume of commodity recovered” is found to be inaccurate, a Supplemental Report is still required.

In those cases in which investigations are ongoing, operators should file a Supplemental Report within one year even in those instances where no new, updated, and/or corrected information has been obtained, indicating such in PART H – Narrative Description of Accident.

For Supplemental Reports filed online, all data previously submitted will automatically populate in the form. Page through the form to make edits and additions where needed.

☐ **Supplemental Report** *plus* ☐ **Final Report**

If an Original Report has already been filed AND new, updated, and/or corrected information is now being submitted via a Supplemental Report, AND the operator is reasonably certain that no further information will be forthcoming, then Final Report is to also be selected along with Supplemental Report. (See also the requirements stated above under “Supplemental Report”.)

Important: If an operator files one of the two types of Final Reports (either Original *plus* Final or Supplemental *plus* Final) and then subsequently finds that new, updated, and/or corrected information needs to be provided, the operator is to submit another Supplemental Report, selecting the appropriate report types (Supplemental or Supplemental *plus* Final)

INSTRUCTIONS FOR FORM PHMSA F 7000-1 (Rev. 10-2011)
ACCIDENT REPORT – HAZARDOUS LIQUID PIPELINE SYSTEMS

for the newly submitted report and explaining the circumstances in PART H – Narrative Description of the Accident.

Required Fields for Small Releases:

If the release is at least 5 gallons but is less than 5 barrels with no additional consequences (see below), complete only the fields indicated by light-grey shading. If the spill is to water as described in §195.52(a)(4) or is otherwise reportable under §195.50, then the entire Form PHMSA F 7000-1 must be completed.

The entire form must be completed for any release that:

- Involves death or personal injury requiring hospitalization; or
- Involves fire or explosion; or
- Is 5 barrels or more; or
- Has property damage greater than \$50,000; or
- Results in pollution of a body of water; or
- In the judgment of the operator was significant even though it did not meet these criteria.

In Part A, answer Questions 1 thru 18 by providing the requested information or by making the appropriate selection.

1. Operator's OPS -Issued Operator Identification Number (OPID)

The Pipeline and Hazardous Materials Safety Administration (PHMSA) assigns the Operator Identification Number (OPID). Most OPIDs are 5 digits. Older OPIDs may contain fewer digits. If your OPID contains fewer than 5 digits, insert leading zeros to fill all blanks. Contact PHMSA's Information Resources Manager at 202-366-8075 if you need assistance with an OPID. Business hours are 8:30 AM to 5:00 PM Eastern Standard Time.

2. Name of Operator

This is the company name used when registering for an OPID and PIN in PHMSA's Online Data Entry System. For online entries, the Name of Operator will be automatically filled in based on the OPID entered in Question 1. If the name that appears does not coincide with the OPID entered, contact PHMSA's Information Resources Manager at 202-366-8075.

3. Address of Operator

Enter the address of the operator's business office to which any correspondence related to the accident report should be sent.

4. Local time (24-hour clock) and date of the Accident

Enter the date of the accident and the local time the accident occurred.

See “Special Instructions”, numbers 9 and 10 for examples of **Date format** and **Time format** expressed as a 24-hour clock.

5. Location of Accident

The latitude and longitude of the accident are to be reported as Decimal Degrees with a minimum of 5 decimal places (e.g. Lat: 38.89664 Long: -77.04327), using the NAD83 or WGS84 datums.

If you have coordinates in degrees/minutes or degrees/minutes/seconds use the formula below to convert to decimal degrees:

$$\text{degrees} + (\text{minutes}/60) + (\text{seconds}/3600) = \text{decimal degrees}$$

e.g. $38^{\circ} 53' 47.904'' = 38 + (53/60) + (47.904/3600) = 38.89664^{\circ}$

All locations in the United States will have a negative longitude coordinate, **which has already been included on the data entry form so that operators do not have to enter the negative sign.**

If you cannot locate the accident with a GPS or some other means, there are online tools that may assist you at <http://www.getlatlon.com/> or <http://viewer.nationalmap.gov/viewer/>. Any questions regarding the required format, conversion, or how to use the tools noted above can be directed to Amy Nelson (202-493-0591 or amy.nelson@dot.gov).

6. National Response Center (NRC) Report Number

Accidents meeting the criteria outlined in §195.52 are to be reported directly to the **24-hour National Response Center (NRC) at 1-800-424-8802** at the earliest practicable moment (generally within 2 hours). The NRC assigns numbers to each call. The number assigned to that Immediate Notice (sometimes referred to as the “Telephonic Report”) is to be entered in Question 6.

7. Local time (24-hr clock) and date of initial telephonic report to the National Response Center

Enter the time and date of the Immediate Notice of the accident to the NRC. The time is to be shown by 24-hour clock notation, and is to reflect the time in the time zone where the accident was physically located. (See “Special Instructions”, numbers 9 and 10.)

8. Commodity Released

Select only one primary description of the commodity and then, where applicable, the secondary description of the commodity, based on the predominant volume released. Only releases of transported commodities are reportable.

☐ **Crude Oil**

☐ **Refined and/or Petroleum Product (non-HVL) which is a Liquid at Ambient Conditions**

Refined and/or Petroleum Product includes gasoline, diesel, jet fuel, kerosene, fuel oils, or other refined or petroleum products which are a liquid at ambient conditions. They are flammable, toxic, or corrosive products obtained from distilling or processing of crude oil, unfinished oils, natural gas liquids, blend stocks, and other miscellaneous hydrocarbon compounds. For a non-HVL petrochemical feedstock, such as propylene, report as “other” and specify the name of the commodity (e.g., “propylene”) in the space provided.

☐ **HVL or Other Flammable or Toxic Fluid which is a Gas at Ambient Conditions**

Highly Volatile Liquids (HVLs) are hazardous liquids or liquid mixtures which will form a vapor cloud when released to the atmosphere and have a vapor pressure exceeding 276 kPa at 37.8 C.

Other Flammable or Toxic Fluids are those defined under 49 CFR 173.120 Class 3—Definitions

Other flammable or toxic fluids which fall under this category include gases at ambient conditions, such as anhydrous ammonia (NH₃) and propane. For a petrochemical feedstock, such as ethane or ethylene, which is also classified as a highly volatile liquid, report as “Other HVL” and specify the appropriate name (e.g., “ethane” or “ethylene”) in the space provided.

☐ **CO₂ (Carbon Dioxide)**

☐ **Biofuel/Alternate Fuel (including ethanol blends)**

Fuel Grade Ethanol is denatured ethanol before it has been mixed with a petroleum product or other hydrocarbon; sometimes also referred to as neat ethanol.

Ethanol Blend is ethanol plus a petroleum product such as gasoline. Such mixtures may be referred to as E10 or E85, for example, representing a 10% or 85% blend respectively. In the space provided, specify the percentage of ethanol in the mixture. Blends greater than 95% ethanol should be reported as Fuel Grade Ethanol.

INSTRUCTIONS FOR FORM PHMSA F 7000-1 (Rev. 10-2011)
ACCIDENT REPORT – HAZARDOUS LIQUID PIPELINE SYSTEMS

Biodiesel is a diesel liquid distilled from biological feedstocks vs. crude oil. Biodiesel is typically shipped as a blend mixed with a petroleum product. Report the percentage biodiesel in the blend as shown. For pure biodiesel, report 100.

General Information for Questions 9, 10, and 11:

Estimate volumes in barrels. Barrel means a unit of measurement equal to 42 U.S. standard gallons. If less than 1 barrel, report to 1 decimal place using the conversion table below. De minimus volumes, including but not limited to those which sometimes result in some form of ignition, are to be reported as 0.1 barrels.

If estimated volume is	Report	If estimated volume is	Report
<5 gallons	0.1 barrels	24-27 gallons	0.6 barrels
5-10 gallons	0.2 barrels	28-31 gallons	0.7 barrels
11-14 gallons	0.3 barrels	32-35 gallons	0.8 barrels
15-18 gallons	0.4 barrels	36-39 gallons	0.9 barrels
19-23 gallons	0.5 barrels	40-42 gallons	1.0 barrels

General Information for Questions 9 and 10:

Important Note: Volumes consumed by fire and/or explosion are to be included in the estimated volumes reported.

9. Estimated volume of commodity released unintentionally

An estimate of the volume released may be based on a variety and/or combination of inputs, including:

- calculations made by hydraulic engineers
- volume added to the pipeline segment to repack the line when the line is placed back in service
- measured volume of free phase commodity recovered, with allowances for commodity that is not recovered.
- volume calculated to be absorbed by soil or water
- volume calculated to have been lost to evaporation (e.g., for gasoline spills)

Estimate the amount of commodity that was released from the beginning of the accident until such time as the commodity is no longer being released from the system.

10. Estimated volume of intentional and/or controlled release/blowdown

Estimate the amount of commodity that was released during any intentional release or controlled blowdown conducted as part of responding to or recovering from the accident. Intentional and controlled blowdown implies a level of control of the site and situation by the operator such that the area and the public are protected during the controlled release.

11. Estimated volume of commodity recovered

Recovered means the commodity is no longer in the environment. The commodity could have been removed by: absorbent pads or similar mechanisms; transferring to temporary storage such as a vacuum truck, a frac tank, or similar vessel; soil removal; bio-remediation; or other similar means of removal or recovery. The volume can be estimated based on a variety or combination of the measurement of free phase commodity recovered, the amount calculated to be absorbed by soil or water that was removed from the environment, measurement of oil extracted from absorbent pads, etc.

12. Were there fatalities?

If a person dies at the time of the accident or within 30 days of the initial accident date due to injuries sustained as a result of the accident, report as a fatality. If a person dies subsequent to an injury more than 30 days past the accident date, report as an injury. (Note: This aligns with the Department of Transportation's general guidelines for all jurisdictional transportation modes for reporting deaths and injuries.)

Contractor employees working for the operator are individuals hired to work for or on behalf of the operator of the pipeline. These individuals are not to be reported as “Operator employees”.

Non-Operator emergency responders are individuals responding to render professional aid at the accident scene including on-duty and volunteer fire fighters, rescue workers, EMTs, police officers, etc. “Good Samaritans” that stop to assist should be reported as “General public.”

Workers Working on the Right of Way, but NOT Associated with this Operator means people authorized to work in or near the right-of-way, but not hired by or working on behalf of the operator of the pipeline. This includes all work conducted within the right-of-way including work associated with other underground facilities sharing the right-of-way, building/road construction in or across the right-of-way, or farming. This category most often includes employees of other pipelines or underground facilities operators, or their contractors, working in or near a shared right-of-way. Workers performing work near, but not on, the right-of-way and who are affected should be reported as “General public”.

13. Were there injuries requiring inpatient hospitalization?

Injuries requiring inpatient hospitalization are injuries sustained as a result of the accident which require both hospital admission *and* at least one overnight stay.

See Question 12 for additional definitions that apply.

14. Was the pipeline/facility shut down due to the Accident?

Report any shutdowns that occur as a result of the accident, including but not limited to those required for damage assessment, temporary repair, permanent repair, and clean-up.

If No is selected, explain the reason that no shutdown was needed in the space provided.

If Yes is selected, complete questions 14.a and 14.b.

14.a. Local time (24hr clock) and date of shutdown

14.b. Local time pipeline/facility restarted

The time is to be shown by 24-hour clock notation, and is to reflect the time in the time zone where the accident was physically located. (See “Special Instructions”, numbers 9 and 10.) Enter the time and date of the shutdown that is associated with the onset or occurrence of the accident in 14.a and the time and date of restart in 14.b. The intent with this data is to capture the total time that the pipeline or facility is shutdown due to the accident. If the pipeline or facility has not been restarted at the time of reporting, select “Still shut down” for Question 14.b and then include the restart time and date in a future Supplemental Report.

15. Did the Commodity Ignite?

Ignite means the released commodity caught fire.

16. Did the Commodity Explode?

Explode means the ignition of the released commodity occurred with a sudden and violent release of energy.

17. Number of general public evacuated

The number of people evacuated is to be estimated based on operator knowledge, or police, fire department, or other emergency responder reports. If there was no evacuation involving the general public, report zero (0). If an estimate is not possible for some reason, leave the field blank but include an explanation of why it was not possible to provide a number in PART H – Narrative Description of the Accident.

18. Time sequence (use local time, 24-hour clock)

Enter the time and date the operator became aware of the accident (i.e., when the operator first identified that the accident had occurred, and NOT when the operator determined that the accident met the reporting criteria of §195.50) and the time operator personnel or contract resources (i.e., personnel or equipment) arrived on site. The time is to be shown by 24-hour clock notation, and is to reflect the time in the time zone where the accident was physically located. (See “Special Instructions”, numbers 9 and 10.)

PART B – ADDITIONAL LOCATION INFORMATION

1. Was the origin of the accident onshore?

Answer Yes or No as appropriate and complete only the designated questions.

If Onshore

2 – 5. Accident Location

Provide the state, zip code, city, and county/parish in which the accident occurred.

6. Operator-designated Location

This is intended to be the designation that the operator would use to identify the location of the accident on its pipeline system. Enter the appropriate milepost/valve station or survey station number. This designator is intended to allow PHMSA personnel to both return to the physical location of the accident using the operator’s own maps and identification systems as well as to identify the “paper” location of the accident when reviewing operator maps and records.

7. Pipeline/Facility Name

Multiple pipeline systems and/or facilities are often operated by a single operator. This information identifies the particular pipeline system or pipeline facility name commonly used by the operator on which the accident occurred, for example, the “West Line 24” Pipeline”, or “Gulf Coast Pipeline”, or “Wooster Terminal”.

8. Segment name/ID

Within a given pipeline system and/or facility, there are typically multiple segment or station identifiers, names, or ID’s which are commonly used by the operator. The information reported here helps locate and/or record the more precise accident location, for example, “Segment 4-32”, or “MP 4.5 to Wayne County Line”, or “Dublin Pump Station”, or “Witte Meter Station”.

9. Was the Accident on Federal Lands other than Outer Continental Shelf?

Federal Lands other than Outer Continental Shelf means all lands the United States owns, including military reservations, except lands in National Parks and lands held in trust for Native Americans. Accidents at Federal buildings, such as Federal Court Houses, Custom Houses, and other Federal office buildings and warehouses, are NOT to be reported as being on Federal Lands.

10. Location of Accident

Operator-controlled Property would normally apply to an operator's facility, which may or may not have controlled access, but which is often fenced or otherwise marked with discernible boundaries. This "operator-controlled property" does not refer to the pipeline right-of-way, which is a separate choice for this question.

11. Area of Accident (as found)

This refers to the location on the pipeline at which commodity was released, resulting in the accident. It does not refer to adjacent locations in which released commodity may have accumulated or ignited.

Underground means pipe, components, or other facilities installed below the natural ground level, road bed, or below the underwater natural bottom.

Under pavement includes under streets, sidewalks, paved roads, driveways, and parking lots.

Exposed due to Excavation means that a normally buried pipeline had been exposed by any party (operator, operator's contractor, or third party) preparatory to or as a result of excavation. The cause of the release, however, may or may not necessarily be related to excavation damage. This category could include a corrosion leak not previously evidenced by stained vegetation, but found during an ILI dig, or a release caused by a non-excavation vehicle where contact happened to occur while the pipeline was exposed for a repair or examination. Natural forces might also damage a pipeline that happened to be temporarily exposed. In each case, the cause should be appropriately reported in PART G of this form.

Aboveground means pipe, components, or other facilities that are above the natural grade.

Typical aboveground facility piping includes any pipe or components installed aboveground such as those at pump stations, valve sites, and breakout tank farms.

Transition area means the junction of differing material or media between pipes, components, or facilities such as those installed at a belowground-aboveground junction (soil/air interface), another environmental interface, or in close contact to supporting elements such as those at water crossings, pump stations and break out tank farms.

12. Did Accident occur in a crossing?

Use **Bridge Crossing** if the pipeline is suspended above a body of water or roadway, railroad right-of-way, etc., either on a separately designed pipeline bridge or as a part of or connected to a road, railroad, or passenger bridge.

Use **Railroad Crossing** or **Road Crossing**, as appropriate, if the pipeline is buried beneath rail bed or road bed.

Use **Water Crossing** if the pipeline is in the water, beneath the water, in contact with the natural ground of the lake bed, etc., or buried beneath the bed of a lake, reservoir, stream or creek, whether the crossing happens to be flowing water at the time of the accident or not. The name of the body of water should be provided if it is commonly known and understood among the local population. (The purpose of this information is to allow persons familiar with the area in which the accident occurred to identify the location and understand it in its local context. Research to identify names that are not commonly used is not necessary since such names would not fulfill the intended purpose. If a body of water does not have a name that is commonly used and understood in the local area, this field may be left blank).

For **Approximate Water Depth (ft)** of the lake, reservoir, etc., estimate the typical water depth at the location of the accident, ignoring seasonal, weather-related, and other factors which may affect the water depth from time to time.

If Offshore

13. Approximate water depth (ft.), at the point of the Accident

This is be the estimated depth from the surface of the water to the seabed at the point of the accident regardless of whether the pipeline is below/on the bottom, underwater but suspended above the bottom, or above the surface (e.g., on a platform).

14. Origin of the Accident

Area and Tract/Block numbers are to be provided for either State or OCS waters, whichever is applicable.

For Nearest County/Parish, as with the name of an onshore body of water (see Question 12 above), the data collected is intended to allow persons familiar with the area in which the accident occurred to identify the location and understand it in its local context. Accordingly, it is not necessary to take measurements to determine which county/parish is “nearest” in cases where the accident location is approximately equidistant from two (or more). In such cases, the name of one of the nearby counties/parishes is to be provided.

PART C – ADDITIONAL FACILITY INFORMATION

1. Is the pipeline or facility [Interstate or Intrastate]?

As defined in section 195.2, **Interstate pipeline** means a pipeline or that part of a pipeline that is used in transportation of hazardous liquids or carbon dioxide in interstate or foreign commerce.

As defined in section 195.2, **Intrastate pipeline** means a pipeline or that part of a pipeline to which Part 195 applies that is not an interstate pipeline.

Operators may refer to Appendix A of Part 195 for further guidance.

3. Item involved in Accident

Pipe (whether pipe body or pipe seam) means the pipe through which the commodity is transported, not including auxiliary piping, tubing or instrumentation.

Nominal diameter of pipe is also called **Nominal pipe size**. It is the diameter in whole number inches (except for pipe less than 4") used to describe the pipe size; for example, 8-5/8 pipe has a nominal pipe size of 8". Decimals are unnecessary for this measure (except for pipe less than 4").

Enter **pipe wall thickness** in inches. Wall thickness is typically less than an inch, and is standard among different pipeline types and manufacturers. Accordingly, use three decimal places to report wall thickness: 0.312, 0.281, etc.

SMYS means specified minimum yield strength and is the yield strength prescribed by the specification under which the material is purchased from the manufacturer.

Pipe Specification is the specification to which the pipe was manufactured, such as API 5L or ASTM A106.

Pipe seam means the longitudinal seam (longitudinal weld) created during manufacture of the joint of pipe.

Pipe Seam Type Abbreviations

SAW means submerged arc weld

ERW means electric-resistance weld

DSAW means double submerged arc weld

Auxiliary piping means piping, usually small in diameter that supports the operation of the mainline or facility piping and does not include tubing. Examples of auxiliary piping include discharge and drain lines, sample lines, etc.

INSTRUCTIONS FOR FORM PHMSA F 7000-1 (Rev. 10-2011)
ACCIDENT REPORT – HAZARDOUS LIQUID PIPELINE SYSTEMS

If the accident occurred on an item not provided in this section, select “Other” and specify the item that failed in the space provided.

6. Type of Accident involved (*select only one*)

Mechanical puncture means a puncture of the pipeline, typically by a piece of equipment such as would occur if the pipeline were pierced by directional drilling or a backhoe bucket tooth. Not all excavation-related damage will be a “mechanical puncture.” (Precise measurement of size – e.g., micrometer – is not needed. Approximate measurements can be provided in inches and one decimal.)

Leak means a failure resulting in an unintentional release of the transported commodity that is often small in size, usually resulting in a low flow release of low volume, although large volume leaks can and do occur on occasion.

Rupture means a loss of containment that immediately impairs the operation of the pipeline. Pipeline ruptures often result in a higher flow release of larger volume. The terms “circumferential” and “longitudinal” refer to the general direction or orientation of the rupture relative the pipe’s axis. They do not exclusively refer to a failure involving a circumferential weld such as a girth weld, or to a failure involving a longitudinal weld such as a pipe seam. (Precise measurement of size – e.g., micrometer – is not needed. Approximate measurements can be provided in inches and one decimal.)

PART D – ADDITIONAL CONSEQUENCE INFORMATION
--

Per 195.450, High Consequence Area means:

- 1. A *commercially navigable waterway*, which means a waterway where a substantial likelihood of commercial navigation exists;**
- 2. A *high population area*, which means an urbanized area as defined and delineated by the Census Bureau that contains 50,000 or more people and has a population density of at least 1,000 people per square mile;**
- 3. An *other populated area*, which means a place as defined and delineated by the Census Bureau that contains a concentrated population, such as an incorporated or unincorporated city, town, village, or other designated residential or commercial area;**
- 4. An *unusually sensitive area*, as defined in §195.6**

* * * * *

5.b Estimated amount released in or reaching water

An estimate of the volume released in or reaching water may be based on a variety and/or combination of inputs, including those mentioned above for PART A, Questions 9 and 10.

5.c Name of body of water, if commonly known:

The name of the body of water should be provided if it is commonly known and understood among the local population. (The purpose of this information is to allow persons familiar with the area in which the accident occurred to identify the location and understand it in its local context. Research to identify names that are not commonly used is not necessary since such names would not fulfill the intended purpose. If a body of water does not have a name that is commonly used and understood in the local area, this field should be left blank).

6. At the location of this Accident, had the pipeline segment or facility been identified as one that “could affect” a High Consequence Area (HCA) as determined in the Operator’s Integrity Management Program?

This question should be answered based on the classification of the involved segment in the operator’s integrity management (IM) program at the time of the accident, whether or not consequences to an HCA ensued. It is possible that a release on a pipeline segment that “could affect” an HCA might not actually affect an HCA. It is also possible that releases from segments thought not able to affect an HCA might have such an affect. This could indicate a deficiency in the operator’s IM program for identifying segments that can affect HCAs, and all of this information is useful for PHMSA’s overall evaluations concerning the efficacy of IM regulation.

7. Did the released commodity reach or occur in one or more High Consequence Area (HCA)?

Guidance available from the pipeline industry for its own spill reporting system is pertinent here. Please see <http://committees.api.org/pipeline/ppts/docs/Advisories/2004-1AdvisoryHCAReporting.pdf>

Generally, a spilled commodity will have “reached” an HCA if the spill zone intersects the boundaries of the HCA polygon as mapped by the National Pipeline Mapping System. The HCA maps should be available as a part of each operator’s Integrity Management Program as per §195.452.

7.a. HCA Type (select all that apply)

Refer to the definitions in §192.450, reproduced above. Leave this question blank if the released commodity did not reach or occur in a High Consequence Area.

8. Estimated Property Damage

All relevant costs available at the time of submission must be included on the initial written Accident Report as well as being updated as needed on Supplemental Reports. This includes (but is not limited to) costs due to property damage to the operator’s facilities and to the property of others, commodity lost, facility repair and replacement, and environmental cleanup and damage. Do NOT include costs incurred for facility repair, replacement, or change that are NOT related to the accident and which are typically done

INSTRUCTIONS FOR FORM PHMSA F 7000-1 (Rev. 10-2011)
ACCIDENT REPORT – HAZARDOUS LIQUID PIPELINE SYSTEMS

solely for convenience. An example of doing work solely for convenience is working on non-leaking facilities unearthed because of the accident. Litigation and other legal expenses related to the accident are not reportable.

Operators are to report costs based on the best estimate available at the time a report is submitted. It is likely that an estimate of final repair costs may not be available when the initial report must be submitted (30 days, per §195.54). The best available estimate of these costs should be included in the initial report. For convenience, this estimate can be revised, if needed, when Supplemental Reports are filed for other reasons, however, when no other changes are forthcoming, Supplemental Reports are to be filed as new cost information becomes available. If Supplemental Reports are not submitted for other reasons, a Supplemental Report is to be filed for the purpose of updating or correcting the estimated cost if these costs differ from those already reported by 20 percent or \$20,000, whichever is greater.

Public and Non-operator private property damage estimates generally include physical damage to the property of others, the cost of environmental investigation and remediation of a site not owned or operated by the operator, laboratory costs, third party expenses such as engineers or scientists, and other reasonable costs, excluding litigation and other legal expenses related to the accident.

Cost of commodity lost includes the cost of the commodity not recovered and/or the cost of recovered commodity downgraded to a lower value or re-processed, and is to be based on the volume reported in PART A, Questions 9, 10, and 11.

Operator's property damage estimates generally include physical damage to the property of the operator or owner company such as the estimated installed or replacement value of the damaged pipe, coating, component, materials, or equipment due to the accident, excluding litigation and other legal expenses related to the accident.

When estimating the **Cost of repairs** to company facilities, the standard shall be the cost necessary to safely restore property to its predefined level of service. Property damage estimates include the cost to access, excavate, and repair the pipeline using methods, materials, and labor necessary to re-establish operations at a predetermined level. These costs may include the cost of repair sleeves or clamps, re-routing of piping, or the removal from service of an appurtenance, tank, or pipeline component. When more comprehensive repairs or improvements are justified but not required for continued operation, the cost of such repairs or replacement is not attributable to the accident. Costs associated with improvements to the pipeline or other facilities to mitigate the risk of future failures are not included.

The following examples are provided for clarity and guidance:

Tank accident - Property damage estimates would include the cost to remove the tank from service, sufficiently clean the tank, repair the tank to a standard operating capability, and then return the tank to service. Costs

INSTRUCTIONS FOR FORM PHMSA F 7000-1 (Rev. 10-2011)
ACCIDENT REPORT – HAZARDOUS LIQUID PIPELINE SYSTEMS

associated with improvements to the tank to mitigate the risk of future failures are not included.

Pipeline accident - Property damage estimates include the cost to access, excavate and repair the pipeline using methods, materials, and labor necessary to re-establish operations at a predetermined level. Costs associated with improvements to the pipeline to mitigate the risk of future failures are not included.

Estimated costs of **Operator's emergency response** include emergency response operations necessary to return the accident site to a safe state, actions to minimize the volume of commodity released, conduct reconnaissance, identify the extent of accident impacts, and contain, control, mitigate, recover, and remove the commodity from the environment, to the maximum extent practicable. They include materials, supplies, labor, and benefits. Costs related to stakeholder outreach, media response, etc. are not to be included. The estimated costs of long-term remediation activities should be included in Environmental Remediation estimates.

Environmental remediation includes the estimated cost to remediate a site such as those associated with engineering, scientists, laboratory costs, and the installation, operation, and maintenance of long-term recovery systems, etc.

Other costs are to include any and all costs which are not included above. Operators are to NOT use this category to report any costs which belong in cost categories separately listed above.

Costs are to be reported in only one category and are not to be double-counted. Costs can be split between two or more categories when they overlap more than one reporting category.

PART E – ADDITIONAL OPERATING INFORMATION

4. Not including pressure reductions required by PHMSA regulations (such as for repairs and pipe movement), was the system or facility relating to the Accident operating under an established pressure restriction with pressure limits below those normally allowed by the MOP?

Consider both voluntary and mandated pressure restrictions. A pressure restriction is to be considered mandated by PHMSA or a state regulator if it was directed by an order or other formal correspondence. Pressure reductions imposed by the operator as a result of regulatory requirements, e.g., a pressure reduction taken because an anomaly identified during an IM assessment could not be repaired within the required schedule (§195.452(h)(3)), is not to be considered mandated by PHMSA.

5.a. Type of upstream valve used to initially isolate release source

Identify the type of valve used to initially isolate the release on the upstream side. In general, this will be the first upstream valve selected by the operator to minimize the release volume but may not be the closest to the accident site or the one that was eventually used for the final isolation of the release site for repair.

5.b. Type of downstream valve used to initially isolate release source

Identify the type of valve used to initially isolate the release on the downstream side. In general, this will be the first downstream valve selected by the operator to minimize the release volume but may not be the closest to the accident site or the one that was eventually used for the final isolation of the release site for repair.

5.c. Length of segment isolated between valves (ft)

Identify the length in feet between the valves identified in Questions 5.a and 5.b that were initially used to isolate the spill area.

5.f. Function of pipeline system

Gathering means a crude oil pipeline 8-5/8 inches or less nominal outside diameter that transports petroleum from a production facility.

Trunkline/Transmission means all other pipeline assets not meeting the gathering definition.

SMYS means specified minimum yield strength and is the yield strength prescribed by the specification under which the material is purchased from the manufacturer.

6. Was a Supervisory Control and Data Acquisition (SCADA)-based system in place on the pipeline or facility involved in the Accident?

This does not mean a system designed or used exclusively for leak detection.

6.a. Was it operating at the time of the Accident?

Was the SCADA system in operation at the time of the accident?

6.b. Was it fully functional at the time of the Accident?

Was the SCADA system capable of performing all of its functions, whether or not it was actually in operation at the time of the accident? If No, describe functions that were not operational in PART H – Narrative Description of the Accident.

6.c and d. Did SCADA-based information (such as alarm(s), alert(s), event(s), and/or volume calculations) assist with the detection (or confirmation) of the Accident?

INSTRUCTIONS FOR FORM PHMSA F 7000-1 (Rev. 10-2011)
ACCIDENT REPORT – HAZARDOUS LIQUID PIPELINE SYSTEMS

Select Yes if SCADA-based information was used to confirm the accident even if the initial report or identification may have come from other sources. Use of SCADA data for subsequent estimation of amount of commodity lost, etc. is not considered use to confirm the accident.

Select No if SCADA-based information was not used to assist with identification of the accident.

7. Was a CPM leak detection system in place on the pipeline or facility involved in the Accident?

This means a system designed and used exclusively for leak detection.

Follow instructions for Question 6 above.

8. How was the Accident initially identified for the Operator? (*select only one*)

Controller per the definition in API RP 1168 means a qualified individual whose function within a shift is to remotely monitor and/or control the operations of entire or multiple sections of pipeline systems via a SCADA system from a pipeline control room, and who has operational authority and accountability for the daily remote operational functions of pipeline systems.

Local Operating Personnel including contractors means employees or contractors working on behalf of the operator outside the control room.

9. Was an investigation initiated into whether or not the controller(s) or control room issues were the cause of or a contributing factor to the Accident?

Select only one of the choices to indicate whether an investigation was/is being conducted (Yes) or was not conducted (No). If an investigation has been completed, select all the factors that apply in describing the results of the investigation.

Cause means an action or lack of action that directly led to or resulted in the pipeline accident.

Contributing factor means an action or lack of action that when added to the existing pipeline circumstances heightened the likelihood of the release or added to the impact of the release.

Controller Error means that the controller failed to identify a circumstance indicative of a release event, such as an abnormal operating condition, alarm, pressure drop, change in flow rate, or other similar event.

INSTRUCTIONS FOR FORM PHMSA F 7000-1 (Rev. 10-2011)
ACCIDENT REPORT – HAZARDOUS LIQUID PIPELINE SYSTEMS

Incorrect Controller action means that the controller errantly operated the means for controlling an event. Examples include opening or closing the wrong valve, or hitting the wrong switch or button.

PART F – DRUG & ALCOHOL TESTING INFORMATION

Requirements for post-accident drug and alcohol tests are in 49 CFR §199.105 and §195.225 respectively. If the accident circumstances were such that tests were not required by these regulations, and if no tests were conducted, select No. If tests were administered, select Yes and report separately the number of operator employees and number of contractors working for the operator who were tested and the number of each that failed such tests.

PART G – APPARENT CAUSE

PART G – Apparent Cause

Select the one, single sub-cause listed under sections G1 thru G8 that best describes the apparent cause of the Accident. These sub-causes are contained in the shaded column on the left under each main cause category. Answer the corresponding questions that accompany your selected sub-cause, and describe any secondary, contributing, or root causes of the Accident in PART H – Narrative Description of the Accident.

G1 – Corrosion Failure

Corrosion includes a release or failure caused by galvanic, atmospheric, stray current, microbiological, or other corrosive action. A corrosion release or failure is not limited to a hole in the pipe or other piece of equipment. If the bonnet or packing gland on a valve or flange on piping deteriorates or becomes loose and leaks due to corrosion and failure of bolts, it is to be classified as Corrosion. (Note: If the bonnet, packing, or other gasket has deteriorated to failure, whether before or after the end of its expected life, but not due to corrosive action, it is to be classified under G6 - Equipment Failure.)

External Corrosion

4.a. Under cathodic protection means cathodic protection in accordance with §195.563 or §195.573(b). Recognizing that older pipelines may have had cathodic protection added over a number of years, provide an estimate if the exact year cathodic protection started is unknown.

Internal Corrosion

9. Location of corrosion

A **low point in pipe** includes portions of the pipe contour in which water might settle out. This includes, but is not limited to, the low point of vertical bends at a crossing of a foreign line or road/railroad, etc., an elbow, a drop out or low point drain.

10. Was the commodity treated with corrosion inhibitors or biocides?

Select Yes if corrosion inhibitors or biocides were included in the commodities transported.

12. Were cleaning/dewatering pigs (or other operations) routinely utilized?

13. Were corrosion coupons routinely utilized?

For purposes of these Questions 12 and 13, “routinely” refers to an action that is performed on more than a sporadic or one-time basis as part of a regular program with the intent to ensure that water build-up and/or settling and internal corrosion do not occur.

Either External or Internal Corrosion

14. List the year of the most recent inspections

Complete this question only when any corrosion failure sub-cause is selected AND the item involved in the accident (as reported in PART C, Question 3) is “Tank/Vessel”. Do not complete if the item involved is Pipe, Weld, or any other item.

15.a. If Yes, for each tool used, select type of internal inspection tool and indicate most recent year run

Magnetic Flux Leakage Tool is an in-line inspection tool using an imposed magnetic flux to detect instances of pipe wall loss from corrosion. Includes low- and high-resolution MFL tools. Does not include transverse flux MFL tools, which are a separate choice in this question.

Ultrasonic refers to an in-line inspection tool that uses ultrasonic technology to measure wall thickness and detect instances of wall loss.

Transverse Field/Triaxial tools are specialized magnetic flux leakage tools that use a flux oriented to improve ability to detect crack anomalies.

Combination Tool refers to any in-line inspection tool that uses a combination of these inspection technologies in a single tool.

16. Has one or more hydrotest or other pressure test been conducted since original construction at the point of the Accident?

Information from the initial post-construction hydrostatic test is not to be reported.

17. Has one or more Direct Assessment been conducted on this segment?

This refers to direct assessment as defined in §195.553. Instances in which one or more indirect monitoring tools (e.g., close interval survey, DCVG) have been used that might be used as part of direct assessment but which were not used as part of the direct assessment process defined in §195.553 do NOT constitute a Direct Assessment for purposes of this question.

G2 – Natural Force Damage

Natural Force Damage includes a release or failure resulting from earth movement, earthquakes, landslides, subsidence, lightning, heavy rains/floods, washouts, flotation, mudslide, scouring, temperature, frost heave, frozen components, high winds, or similar natural causes.

Earth Movement, NOT due to Heavy Rains/Floods refers to accidents caused by land shifts such as earthquakes, subsidence, or landslides, but not mudslides which are presumed to be initiated by heavy rains or floods.

Heavy Rains/Floods refer to all water-related natural force causes. While mudslides involve earth movement, report them here since typically they are an effect of heavy rains or floods.

Lightning includes both damage and/or fire caused by a direct lightning strike and damage and/or fire as a secondary effect from a lightning strike in the area. An example of such a secondary effect would be a forest fire started by lightning that results in damage to a pipeline system asset which results in an accident. (See also the discussion of “secondary ignition” under the *General Instructions*.)

Temperature includes weather-related temperature and thermal stress effects, either heat or cold, where temperature was the initiating cause.

Thermal stress refers to mechanical stress induced in a pipe or component when some or all of its parts are not free to expand or contract in response to changes in temperature.

Frozen components would include accidents where components are inoperable because of freezing and those due to cracking of a piece of equipment due to expansion of water during a freeze cycle.

INSTRUCTIONS FOR FORM PHMSA F 7000-1 (Rev. 10-2011)
ACCIDENT REPORT – HAZARDOUS LIQUID PIPELINE SYSTEMS

High Winds includes damage caused by wind-induced forces. Select this category if the damage is due to the force of the wind itself. Damage caused by impact from objects blown by wind would be reported under G4 - Other Outside Force Damage.

Other Natural Force Damage. Select this sub-cause for types of Natural Force Damage not included otherwise, and describe in the space provided. If necessary, provide additional explanation in PART H – Narrative Description of the Accident.

Answer Questions 6 and 6.a if the accident occurred in conjunction with an extreme weather event such as a hurricane, tropical storm, or tornado. If an extreme weather event related to something other than a hurricane, tropical storm, or tornado was involved, indicate Other and describe the event in the space provided.

G3 – Excavation Damage

Excavation Damage includes a release or failure resulting directly from excavation damage by operator's personnel (oftentimes referred to as "first party" excavation damage) or by the operator's contractor (oftentimes referred to as "second party" excavation damage) or by people or contractors not associated with the operator (oftentimes referred to as "third party" excavation damage). Also, this section includes a release or failure determined to have resulted from previous damage due to excavation activity. For damage from outside forces OTHER than excavation which results in a release, use G2 - Natural Force Damage or G4 - Other Outside Force, as appropriate. Also, for a strike, physical contact, or other damage to a pipeline or facility that apparently was NOT related to excavation and that results in a delayed or eventual release, report the accident under G4 as "Previous Mechanical Damage NOT related to Excavation."

Excavation Damage by Operator (First Party) refers to accidents caused as a result of excavation by a direct employee of the operator.

Excavation Damage by Operator's Contractor (Second Party) refers to accidents caused as a result of excavation by the operator's contractor or agent or other party working for the operator.

Excavation Damage by Third Party refers to accidents caused by excavation damage resulting from actions by personnel or other third parties not working for or acting on behalf of the operator or its agent.

Previous Damage due to Excavation Activity refers to accidents that were apparently caused by prior excavation activity and that then resulted in a delayed or eventual release. Indications of prior excavation activity might come from the condition of the pipe when it is examined, or from records of excavation at the site, or through metallurgical analysis or other inspection and/or testing methods. Dents and gouges in the 10:00-to-2:00 o'clock positions on the pipe, for instance, may indicate an earlier strike, as might marks from the bucket or tracks of an earth moving machine or similar pieces of equipment.

1.a. If Yes, for each tool used, select type of internal inspection tool and indicate most recent year run

Magnetic Flux Leakage Tool is an in-line inspection tool using an imposed magnetic flux to detect instances of pipe wall loss from corrosion. Includes low- and high-resolution MFL tools. Does not include transverse flux MFL tools, which are a separate choice in this question.

Ultrasonic refers to an in-line inspection tool that uses ultrasonic technology to measure wall thickness and detect instances of wall loss.

Transverse Field/Triaxial tools are specialized magnetic flux leakage tools that use a flux oriented to improve ability to detect crack anomalies.

Combination Tool refers to any in-line inspection tool that uses a combination of these inspection technologies in a single tool.

3. Has one or more hydrotest or other pressure test been conducted since original construction at the point of the Accident?

Information from the initial post-construction hydrostatic test is not to be reported.

4. Has one or more Direct Assessment been conducted on this segment?

This refers to direct assessment as defined in §195.553. Instances in which one or more indirect monitoring tools (e.g., close interval survey, DCVG) have been used that might be used as part of direct assessment but which were not used as part of the direct assessment process defined in §195.553 do not constitute a Direct Assessment for purposes of this question.

7. – 17. Complete these questions for any excavation damage sub-cause. Instructions for answering these questions can be found at CGA's web site, <https://www.damagereporting.org/dr/control/userGuide.do>.

G4 – Other Outside Force Damage

Other Outside Force Damage includes, but are not limited to, a release or failure resulting from non-excavation-related outside forces, such as nearby industrial, man-made, or other fire or explosion; damage by vehicles or other equipment; failures due to mechanical damage; and, intentional damage including vandalism and terrorism.

Nearby Industrial, Man-made or other Fire/Explosion as Primary Cause of Accident applies to situations where the fire occurred before - and *caused* - the release. (See also the discussion of “secondary ignition” under the *General Instructions*.) Examples of such an accident would be an explosion or fire at a neighboring facility or installation (chemical

INSTRUCTIONS FOR FORM PHMSA F 7000-1 (Rev. 10-2011)
ACCIDENT REPORT – HAZARDOUS LIQUID PIPELINE SYSTEMS

plant, tank farm, other industrial facility) or structure, debris, or brush/trees that results in a release at the operator's pipeline or facility. This includes forest, brush, or ground fires that are caused by human activity. If the fire, however, is known to have been started as a result of a lightning strike, the accident's cause is to be classified under G2 - Natural Force Damage. Arson events directed at harming the pipeline or the operator should be reported as G4 - Intentional Damage (see below). This sub-cause is NOT to be used if the release occurred first and then the gas released from the pipeline system or facility ignited.

Damage by Car, Truck, or Other Motorized Vehicle/Equipment NOT Engaged in Excavation. An example of this sub-cause would be a stopple tee that releases commodity when damaged by a pickup truck maneuvering near the pipeline. Other motorized vehicles or equipment include tractors, backhoes, bulldozers and other tracked vehicles, and heavy equipment that can move. Include under this sub-cause accidents caused by vehicles operated by the pipeline operator, the pipeline operator's contractor, or a third party, and

specify the vehicle/equipment operator's affiliation from one of these three groups. Pipeline accidents resulting from vehicular traffic loading or other contact should also be reported in this category. If the activity that caused the release involved digging, drilling, boring, grading, cultivation or similar activities, report under G3 - Excavation Damage.

Damage by Boats, Barges, Drilling Rigs, or Other Maritime Equipment or Vessels Set Adrift or Which Have Otherwise Lost Their Mooring. This sub-cause includes impacts by maritime equipment or vessels (including their anchors or anchor chains or other attached equipment) that have lost their moorings and are carried into the pipeline facility by the current. This sub-cause also includes maritime equipment or vessels set adrift as a result of severe weather events and carried into the pipeline facility by waves, currents, or high winds. In such cases, also indicate the type of severe weather event. Do NOT report in this sub-cause accidents which are caused by the impact of maritime equipment or vessels while they are engaged in their normal or routine activities; such accidents are to be reported as "Routine or Normal Fishing or Other Maritime Activity NOT Engaged in Excavation" under this section G4 (see below) so long as those activities are not excavation activities. If those activities are excavation activities such as dredging or bank stabilization or renewal, the accident is to be reported under G3 - Excavation Damage.

Routine or Normal Fishing or Other Maritime Activity NOT Engaged in Excavation. This sub-cause includes accidents due to shrimping, purseining, oil drilling, or oilfield workover rigs, including anchor strikes, and other routine or normal maritime-related activities UNLESS the movement of the maritime asset was due to a severe weather event (this type of accident should be reported under "Damage by Boats, Barges, Drilling Rigs, or Other Maritime Equipment or Vessels Set Adrift or Which Have Otherwise Lost Their Mooring" in this section G4); or the accident was caused by excavation activity such as dredging of waterways or bodies of water (this type of accident is to be reported under G3 - Excavation Damage).

Electrical Arcing from Other Equipment or Facility such as a pole transformer or adjacent facility's electrical equipment.

Previous Mechanical Damage NOT Related to Excavation. This sub-cause covers accidents where damage occurred at some time prior to the release that was apparently NOT related to excavation activities, and would include prior outside force damage of an unknown nature, prior natural force damage, prior damage from other outside forces, and any other previous mechanical damage other than that which was apparently related to prior excavation. Accidents resulting from previous damage sustained during construction, installation, or fabrication of the pipe or weld from which the release eventually occurred are to be reported under G5 - Material Failure of Pipe or Weld. (See this sub-cause for typical indications of previous construction, installation, or fabrication damage.) Accidents resulting from previous damage sustained as a result of excavation activities should be reported under G3 – Previous Damage due to Excavation Activity. (See this sub-cause for typical indications of prior excavation activity.)

Intentional Damage

Vandalism means willful or malicious destruction of the operator's pipeline facility or equipment. This category would include arson, pranks, systematic damage inflicted to harass the operator, motor vehicle damage that was inflicted intentionally, and a variety of other intentional acts. (See also the discussion of "secondary ignition" under the *General Instructions*.)

Terrorism, per 28 CFR §0.85 General Functions, includes the unlawful use of force and violence against persons or property to intimidate or coerce a government, the civilian population, or any segment thereof, in furtherance of political or social objectives. Operators selecting this item are encouraged to also notify the FBI.

Theft of commodity or Theft of equipment means damage by any individual or entity, by any mechanism, specifically to steal, or attempt to steal, the transported commodity or pipeline equipment.

Other Describe in the space provided and, if necessary, provide additional explanation in PART H – Narrative Description of the Accident.

Other Outside Force Damage. Select this sub-cause for types of Other Outside Force Damage not included otherwise, and describe in the space provided. If necessary, provide additional explanation in PART H – Narrative Description of the Accident.

G5 – Material Failure of Pipe or Weld

Use this section to report material failures only if "Item Involved in accident" (PART C, Question 3) is "**Pipe**" (whether "**Pipe Body**" or "**Pipe Seam**") or "**Weld**." Indicate how the sub-cause was determined or if the sub-cause is still being investigated.

INSTRUCTIONS FOR FORM PHMSA F 7000-1 (Rev. 10-2011)
ACCIDENT REPORT – HAZARDOUS LIQUID PIPELINE SYSTEMS

This section includes releases in or failures from defects or anomalies within the material of the pipe body or within the pipe seam or other weld due to faulty manufacturing procedures, defects resulting from poor construction, installation, or fabrication practices, and in-service stresses such as vibration, fatigue, and environmental cracking.

Construction-, Installation-, or Fabrication-related includes a release or failure caused by a dent, gouge, excessive stress, or some other defect or anomaly introduced during the process of constructing, installing, or fabricating pipe and pipe welds, including welding or other activities performed at the facility. Included are releases from or failures of wrinkle bends, field welds, and damage sustained in transportation to the construction or fabrication site. Not included are failures due to seam defects, which are to be reported as Original Manufacturing-related (see below).

Original Manufacturing-related (NOT girth weld or other welds formed in the field) includes a release or failure caused by a defect or anomaly introduced during the process of

manufacturing pipe, including seam defects and defects in the pipe body. This option is not appropriate for wrinkle bends, field welds, girth welds, or other joints fabricated in the field. Use this option for failures such as those due to defects of the longitudinal weld or inclusions in the pipe body.

If **Construction, Installation, Fabrication-related** or **Original Manufacturing-related** is selected, then select any contributing factors. Examples of Mechanical Stress include failures related to overburden or loss of support.

G6 – Equipment Failure

This section applies to failures of items other than “Pipe” (“Pipe Body” or “Pipe Seam”) or “Weld”.

Equipment Failure includes a release or failure resulting from: malfunction of control/relief equipment including valves, regulators, or other instrumentation; failures of compressors, or compressor-related equipment; failures of various types of connectors, connections, and appurtenances; failures of the body of equipment, vessel plate, or other material (including those caused by construction-, installation-, or fabrication-related and original manufacturing-related defects or anomalies); and, all other equipment-related failures.

Malfunction of Control/Relief Equipment. Examples of this type of accident cause include: overpressurization resulting from malfunction of a control or alarm device; relief valve malfunction; valves failing to open or close on command; or valves which opened or closed when not commanded to do so. If overpressurization or some other aspect of this accident was caused by incorrect operation, the accident should be reported under G7 - Incorrect Operation.

ESD System Failure means failure of an emergency shutdown system.

INSTRUCTIONS FOR FORM PHMSA F 7000-1 (Rev. 10-2011)
ACCIDENT REPORT – HAZARDOUS LIQUID PIPELINE SYSTEMS

Other Equipment Failure. Select this sub-cause for types of Equipment Failure not included otherwise, and describe in the space provided. If necessary, provide additional explanation in PART H – Narrative Description of the Accident.

G7 – Incorrect Operation

Incorrect Operation includes a release or failure resulting from operating, maintenance, repair, or other errors by facility personnel, including, but not limited to improper valve selection or operation, inadvertent overpressurization, or improper selection or installation of equipment.

Other Incorrect Operation. Select this sub-cause for types of Incorrect Operation not included otherwise, and describe in the space provided. If necessary, provide additional explanation in PART H – Narrative Description of the Accident.

G8 – Other Accident Cause

This section is provided for accidents whose cause is currently unknown, or where investigation into the cause has been exhausted and the final judgment as to the cause remains unknown, or where a cause has been determined which does not fit into any of the main cause categories listed in sections G1 thru G7.

If the accident cause is known but doesn't fit into any category in sections G1 thru G7, select **Miscellaneous** and enter a description of the accident cause, continuing with a more thorough explanation in PART H - Narrative Description of the Accident.

If the accident cause is unknown at the time of filing this report, select **Unknown** in this section and specify one reason from the accompanying two choices. Once the operator's investigation into the accident cause is completed, the operator is to file a Supplemental Report as soon as practicable either reporting the apparent cause or stating definitively that the cause remains Unknown, along with any other new, updated, and/or corrected information pertaining to the accident. This Supplemental Report is to include all new, updated, and/or corrected information pertaining to *all* portions of the report form known at this time, and not only that information related to the apparent cause.

Important Note: Whether the investigation is completed or not, or if the cause continues to be unknown, Supplemental Reports are to be filed reflecting new, updated, and/or corrected information **as and when this information becomes available**. In those cases in which investigations are ongoing for an extended period of time, operators are to file a Supplemental Report within one year of their last report for the accident even in those instances where no new, updated, and/or corrected information has been obtained, with an explanation that the cause remains under investigation in PART H – Narrative Description of Accident. Additionally, final determination of the apparent cause and/or closure of the

INSTRUCTIONS FOR FORM PHMSA F 7000-1 (Rev. 10-2011)
ACCIDENT REPORT – HAZARDOUS LIQUID PIPELINE SYSTEMS

investigation does NOT preclude the need for the operator's filing of additional Supplemental Reports as and when new, updated, and/or corrected information becomes available.

PART H – NARRATIVE DESCRIPTION OF THE ACCIDENT

Concisely describe the accident, including the facts, circumstances, and conditions that may have contributed directly or indirectly to causing the accident. Include secondary, contributing, or root causes when possible, or any other factors associated with the cause that are deemed pertinent. Use this section to clarify or explain unusual conditions, to provide sketches or drawings, and to explain any estimated data. Operators submitting reports on-line will be afforded the opportunity to attach/upload files (in PDF or JPG format only) containing sketches, drawings, or additional data.

If you selected Miscellaneous in section G8, the narrative is to describe the accident in detail, including all known or suspected causes and possible contributing factors.

PART I – PREPARER AND AUTHORIZED SIGNATURE

The Preparer is the person who compiled the data and prepared the responses to the report and who is to be contacted for more information (preferably the person most knowledgeable about the information in the report or who knows how to contact the person most knowledgeable). Enter the Preparer's e-mail address if the Preparer has one, and the phone and fax numbers used by the Preparer.

An Authorized Signature must be obtained from an officer, manager, or other person whom the operator has designated to review and approve the report. This individual is responsible for assuring the accuracy and completeness of the reported data. In addition to their title, a phone number and email address are to be provided for the individual signing as the Authorized Signature.