

Clarification of usage of Emission Designators in the Private Radio Services

Applicants for licenses in any of the private radio services are reminded *not* to use the new emission designators approved by the Commission last year. The new designators were published in the *Federal Register* December 14, 1984, but the automated license processing system for PRB applications are not yet ready for them.

Applicants should continue to use the old designators until further notice. The old designators for applicants in Parts 81, 83, 87, 90, 94, 95 and 97 are listed in § 2.201 of the Commission's rules, as published in the October 1984 edition of title 47, Code of Federal Regulations (47 CFR).

For information, call the Licensing Division in Gettysburg, Pa., at (717) 337-1212, or Rick Kenney, at (202) 632-6497.

William J. Tricarico,
Secretary, Federal Communications Commission.

[FR Doc. 85-6414 Filed 3-22-85; 8:45 am]

BILLING CODE 6712-01-M

DEPARTMENT OF TRANSPORTATION

Research and Special Programs Administration

49 CFR Parts 172, 173, 178, and 179

[Docket HM-139G; Amdt. Nos. 172-97, 173-187, 178-84, and 179-38]

Conversion of Individual Exemptions Into Regulations of General Applicability

AGENCY: Materials Transportation Bureau (MTB), Research and Special Programs Administration, DOT.

ACTION: Final rule.

SUMMARY: This action is being taken to incorporate into the Department's Hazardous Materials Regulations a number of changes based on the data and analyses supplied in selected exemption applications or from existing exemptions. The need for this action has been created by the public demand to make available new packagings and shipping alternatives that have proven themselves safe under the Department's exemptions program. The intended effect of these amendments is to provide wider access to the benefits of transportation innovations recognized and shown to be effective and safe.

EFFECTIVE DATE: These amendments are effective April 22, 1985. However, compliance with the regulations as

amended herein, is authorized immediately.

FOR FURTHER INFORMATION CONTACT: Darrell L. Raines, Chief, Exemptions and Regulations Termination Branch, Office of Hazardous Materials Regulation, Materials Transportation Bureau, Washington, D.C. 20590 (202)-426-2075.

SUPPLEMENTARY INFORMATION: On August 28, 1984, the MTB published Notice No. 84-9 (49 FR 34044) under Docket HM-139G which proposed to amend the Hazardous Materials Regulations by incorporating the provisions of certain DOT exemptions into the general regulations. The public comment period ended October 31, 1984.

The MTB received fifteen comments from the general public on Notice 84-9.

Five of the commenters expressed their approval and endorsed the changes as proposed. All of the other comments were favorable and a few recommended minor changes.

The majority of the comments received were in reference to DOT-E 8129 and DOT-E 8445 concerning overpacking waste materials for disposal (i.e., "Lab packs"). The suggested comments were as follows:

- (a) Allow more than one hazard class in one outside drum.
- (b) Increase the gross weight from 200 pounds to 450 pounds.
- (c) Eliminate the private or contract motor carrier restriction.
- (d) Require only enough cushioning material to prevent movement or damage to the inner packaging.
- (e) Allow the use of any outside DOT specification container capable of passing the required tests. Also, allow the use of a DOT specification fiberboard box lined with a poly-liner.

One commenter requested that the provisions of DOT-E 9154 become a part of the amendments proposed under Docket No. HM-139G. This exemption authorizes the use of a non-DOT specification steel drum of 19-gauge thickness to be used for those hazardous materials that are authorized to be packaged in a 20/18 gauge, 55-gallon capacity, DOT-17E steel drum.

One commenter requested that DOT-E 9182, DOT-E 9241, and DOT-E 9244 be added as a part of this rulemaking. All three of these exemptions were issued to the same Company for the transportation of "Explosives pest repellent devices".

The last commenter suggested that the proposed shipping name "Explosive pest control devices" authorized by DOT-E 9182, DOT-E 9241, and DOT-E 9244 be changed to "Pyrotechnic wildlife dispersal devices".

Concerning DOT-E 8129 and DOT-E 8445, MTB does not agree that more than one hazard class should be allowed in one outside drum. It is noted that DOT-E 8129 specifically states that each outer packaging must contain only chemically compatible materials on the same hazard class. This restriction does not appear in DOT-E 8445, as presently written. Although we are not aware of the occurrence of any specific transportation compatibility problems under DOT-E 8445, the potential for such problems in both transportation and at the treatment or storage facility exists. The MTB realizes that it may be more convenient and cost effective for a shipper to mix hazard classes when the materials are compatible. Because of added risks of this practice, we do not believe that the regulations should be amended at this time to allow different hazard classes in one outside drum.

The original petitioner of DOT-E 8445 requested that the restriction proposed in § 173.12(d)(1) be deleted because the exemption allows mixing of inside packages of different hazard classes in the same outside packaging as long as the materials are compatible and not capable of evolving a dangerous quantity of heat, gas, or Class A poison, if mixed. As indicated above, the MTB does not agree that this rulemaking should allow the mixing of different hazard classes in a single outside packaging. DOT-E 8445 will not be eliminated by this rulemaking. In view of the fact that mixing different hazard classes in one outside packaging may cause problems at disposal sites, the MTB does not anticipate heavy activity under DOT-E 8445. Also, the suggestion that the materials to which § 173.12 would apply to be limited to those for which exceptions are allowed in § 172.101, column 5(a) is not adopted in this rule.

The maximum gross weight has been increased to 450 pounds or the rated capacity of drum; whichever is less.

The MTB does not agree that the restriction on the use of only private or contract motor carriers should be eliminated. The use of private or contract motor carriers allows better control of the transportation of waste material. After a reasonable period of time, when more transportation experience is received, the MTB may consider authorizing the use of common motor carriers.

The use of only enough cushioning material to prevent movement or damage to the inner packaging may not be a safe practice. If enough cushioning material is used to prevent damage to the inner packaging and to absorb the

liquid contents, there would not be any leakage even if both the inner and outside packagings failed. Considering that the outer packaging may be a fiber drum, this is not an unlikely event. For this reason, MTB is retaining the requirement that enough cushioning material be used to absorb the total liquid contents. Also, the MTB does not agree that expanding the use of outside packagings in addition to those authorized under DOT-E 8129 and DOT-8445 is a safe practice.

The suggestion of one commenter to include the provisions of DOT-E 9154 which authorizes the use of a non-DOT specification steel drum into this rulemaking is denied, but will be considered in Docket HM-181.

Exemptions DOT-E 9182, DOT-E 9241, and DOT-E 9244 were issued after Notice No. 84-9 was published. Although the referenced exemptions require the proper shipping name to be "Explosive pest repellent devices" instead of "Explosive pest control devices", the packaging and explosive contents authorized by DOT-E 7085, DOT-E 8595, and DOT-E 8646 for the transportation of "Explosive pest control

devices" are very similar to the "Explosive Pest Repellent Devices" authorized by DOT-E 9182, DOT-E 9241, and DOT-E 9244. A cursory review indicates that two of the new exemptions may be eliminated by these amendments. A further review is being made to determine exactly how DOT-E 9182, DOT-E 9241, and DOT-E 9244 were affected by these amendments.

The Materials Transportation Bureau has determined that this document is not a "major rule" under the terms of Executive Order 12291 or significant under DOT's regulatory policies and procedures (44 FR 11034). A final regulatory evaluation was not prepared as the economic impact of these amendments has been found to be minimal.

Based on limited information available concerning size and nature of entities likely to be affected by this amendment, I certify that this amendment will not have a significant economic impact on a substantial number of small entities.

The following list of Federal Register Thesaurus of Indexing Terms applies to this rulemaking:

List of Subjects

49 CFR Part 172

Hazardous materials transportation, Labeling, Packaging and containers.

49 CFR Part 173

Hazardous materials transportation, Packaging and containers.

49 CFR Part 178

Hazardous Materials Transportation, Shipping container specifications.

49 CFR Part 179

Hazardous materials transportation, Railroad safety.

In consideration of the foregoing, 49 CFR Parts 172, 173, 178, and 179 are amended as follows:

PART 172—HAZARDOUS MATERIALS TABLES AND HAZARDOUS MATERIALS COMMUNICATIONS REGULATIONS

1. In § 172.101, the Hazardous Materials Table is amended by adding, removing, or revising the following entries:

§ 172.101 Hazardous materials table.

FAW	Hazardous materials descriptions and proper shipping names	Hazard class	Identification number	Label(s) required (if not excepted)	Packaging		Maximum net quantity in one package		Water shipments		
					Excep-tions	Specific require-ments	Passenger carrying aircraft or railcar	Cargo aircraft only	Cargo ves-sel	Pas-senger vessel	Other requirements
(1)	(2)	(3)	3(a)	(4)	5(a)	5(b)	6(a)	6(b)	7(a)	7(b)	7(c)
	ADD Barium styphnate, monohydrate. See Initiating explosive.										
	Explosive pest control devices.	Class C explosive		Explosive C	None	173.100	50 pounds	150 pounds	1,3	1,3	
	Initiating explosive barium styphnate, monohydrate, lead styphnate (lead trinitroresorcinate).	Class A explosive		Explosive A	None	173.74	Forbidden	Forbidden	6	5	
	REMOVE Initiating explosive (lead styphnate (lead trinitroresorcinate)).	Class A explosive		Explosive A	None	173.74	Forbidden	Forbidden	6	5	
	REVISE Carbon bisulfide, or Carbon disulfide (RC 5000/2270).	Flammable liquid	UN1131	Flammable liquid	None	173.121	Forbidden	Forbidden	1	5	Keep cool. Not permitted on any vessel transporting explosives, except that quantities not exceeding 200 pounds may be transported on such vessels under conditions approved by the Captain of the Port.

+EAW	Hazardous materials descriptions and proper shipping names	Hazard class	Identification number	Label(s) required (if not excepted)	Packaging		Maximum net quantity in one package		Water shipments		
					Exceptions	Specific requirements	Passenger carrying aircraft or railcar	Cargo aircraft only	Cargo vessel	Passenger vessel	Other requirements
(1)	(2)	(3)	3(a)	(4)	5(a)	5(b)	6(a)	6(b)	7(a)	7(b)	7(c)
	Nickel carbonyl.....	Flammable liquid....	UN1259.....	Flammable liquid and Poison.	None	173.126	Forbidden.....	Forbidden.....	1	5	Shade from radiant heat. Segregation same as for flammable liquids. Not permitted on a vessel transporting explosives, except that quantities not exceeding 200 pounds may be transported on such vessels under conditions approved by the Captain of the Port.

PART 173—SHIPPERS—GENERAL REQUIREMENTS FOR SHIPMENTS AND PACKAGINGS

2. To add § 173.12 to read follows:

§ 173.12 Exceptions for shipment of waste material.

(a) *General.* Waste material meeting the hazard class definition of a flammable liquid, flammable solid, oxidizer, corrosive material, Posion B or ORM-A, B, C, and E are excepted from the specification packaging requirements of this subchapter if packaged in combination packagings in accordance with this section and transported for disposal or recovery by private or contract motor carrier by highway only. In addition, a generic proper shipping name from § 172.101 may be used in place of specific chemical names, when two or more waste materials in the same hazard class are packaged in the same outside packaging, provided the waste materials are chemically compatible.

(b) *Outside packagings.* The outside packaging must be a DOT specification metal or fiber drum. It may also be a polyethylene drum capable of withstanding: (1) The vibration and compression tests specified in § 178.19-7(c) (1) and (2), except the compression test value must be no less than 2400 pounds, and (2) a four-foot drop test as specified in § 178.19-7(a)(1).

(c) *Inside packagings.* The inside packagings must be either glass packagings not exceeding 1-gallon rated capacity, or metal or plastic packagings not exceeding a rated capacity of 5 gallons.

(d) *Additional packaging requirements.* The following additional requirements are applicable:

(1) Each outside packaging may only contain one hazard class and the materials must be chemically compatible;

(2) Inside packagings of liquid must be surrounded by a compatible absorbent material capable of absorbing the total liquid contents; and

(3) Gross weight may not exceed 450 pounds or the rated capacity of the drum; whichever is less.

(e) *Prohibited materials.* The following materials are not authorized under the provisions of this section: acrolein; bromine pentafluoride; bromine trifluoride; chloric acid, chlorine trifluoride, nitric acid, fuming; pyroforic liquids; and sulfuric acid, fuming.

3. In § 173.74, paragraphs (a), (b), and (c) are revised to read as follows:

§ 173.74 Lead styphnate.

(a) The offering of lead styphnate (lead trinitroresorcinate) or barium styphnate, monohydrate in a dry condition for transportation is forbidden, except as a component of manufactured articles such as percussion caps, detonators, blasting caps, and exploders.

(b) Lead styphnate (lead trinitroresorcinate) or barium styphnate, monohydrate must be packed wet with at least 20 percent by weight of water in a Specification 5 or 5B (§§ 178.80, 178.82 of this subchapter) metal barrel or drum, or a Spec. 17H (§ 178.118 of this subchapter) metal drum (single-trip), lined with a heavy, close-fitting jute bag closed by secure sewing. The lead styphnate (lead trinitroresorcinate) or barium styphnate, monohydrate shall be placed in an inside bag made of rubber or rubberized cloth. This bag should be divided into a number of smaller

packages. Inside the bag and over the lead styphnate, (lead trinitroresorcinate) or barium styphnate, monohydrate there must be placed a cap of the same fabric and of the same diameter as the bag. The bag and contents must be packed in the center of the metal barrel or drum, and must be entirely surrounded by at least three inches of well-packed sawdust saturated with water. The barrel or drum must be inspected carefully and be determined free of leaks. The dry weight of lead styphnate (lead trinitroresorcinate) or barium styphnate, monohydrate in one outside container may not exceed 150 pounds.

(c) If lead styphnate (lead trinitroresorcinate) or barium styphnate, monohydrate is to be transported during freezing weather it must be wet with a mixture of denatured ethyl alcohol and water so that it does not freeze.

4. § 178.100, paragraph (ii) is added to read as follows:

§ 178.100 Definition of Class C explosives.

* * * * *

(ii) Explosive pest control devices, class C explosives, consist of a cardboard-pasteboard type tube not exceeding 4 inches in length and 3/4 inch in diameter or a shotgun shell type having an explosive projectile. They may contain a mixture of potassium perchlorate, aluminum powder, sulfur, black powder, smokeless powder or similiar pyrotechnic mixture. The component which produces the audible effect may not contain more than 40 grains of explosive composition. Devices and packaging must be of a type examined by the Bureau of Explosives of the Bureau of Mines and approved by the Associate Director for HMR.

§ 178.127 [Amended]

5. In § 178.127 the flash point "30 °F." is amended to read "25 °F." at each of the three places it appears.

6. In § 178.133, paragraph (a)(1) is revised; paragraph (a)(2) is added and the introductory text of paragraph (b) is revised to read as follows:

§ 178.133 Spirits of nitroglycerin.

(a) Spirits of nitroglycerin means nitroglycerin in ethyl alcohol or in propylene glycol. Solutions of nitroglycerin means nitroglycerin in acetone. These mixtures and solutions may not contain more than 10 percent by weight of nitroglycerin. They must be packed in specification packings as follows:

(1) Specifications 15A, 15B, 15C, 16A, 19A, or 19B (§§ 178.168, 178.169, 178.170, 178.185, 178.190, 178.191 of this subchapter). Wooden boxes lined with paraffined paper, Spec. 2L (§ 178.30 of this subchapter), and with inside packagings securely closed with rubber stoppers tied in place. The inside packagings must be entirely surrounded by at least 2 inches of dry, fine sawdust or kieselguhr. Not more than 6 quarts of the spirits or solutions may be packed in any outside wooden box. Inside packagings made of metal are not authorized.

(2) Specification 12A or 12B (§§ 178.210 or 178.205 of this subchapter). Fiberboard boxes or Spec. 21C (§ 178.224 of this subchapter) fiber drums laminated with a 0.004 inch polyethylene lining. Inside packagings must be Spec. 2E polyethylene bottles or Spec. 2U polyethylene containers not exceeding 5 gallons capacity each, overpacked in a strong polyethylene bag. The inside packagings must be entirely surrounded by at least 2 inches of dry, fine sawdust or kieselguhr. Not more than 6 quarts of the nitroglycerin mixture may be packed in one outside packaging, except that a maximum of 5 gallons of a nitroglycerin-propylene glycol mixture may be packaged in one Spec. 2U and overpacked in the fiber drum.

(b) Spirits of nitroglycerin consisting of not over 1 percent by weight of nitroglycerin in ethyl alcohol or propylene glycol, in addition to containers specified in paragraphs (a)(1) and (a)(2) of this section, may be packed in specification packagings as follows:

7. In § 173.164, paragraph (a)(6) is revised to read as follows:

§ 173.164 Chromic acid or chromic acid mixture, dry.

(a) * * *

(6) Specification 21C (§ 178.224 of this subchapter). Fiber drums lined with a plastic material having a minimum thickness of 0.003-inch. Net weight may not exceed 115 pounds.

8. In § 173.217, paragraphs (a)(3), (a)(6), and (a)(8) are revised to read as follows:

§ 173.217 Calcium hypochlorite, hydrated; calcium hypochlorite mixture, dry; lithium hypochlorite mixture, dry; mono-(trichloro) tetra-(monopotassium dichloro)-penta-s-triazinetrione, dry; potassium dichloro-s-triazinetrione, dry; sodium dichloro-s-triazinetrione, dry; trichloro-s-triazinetrione, dry.

(a) * * *

(3) Specification 21C (§ 178.224 of this subchapter). Fiber drums with inner ply consisting of a laminated sheet of paper and aluminum foil, internally coated. Cover of drum must be gasketed. Authorized net weight not over 400 pounds.

(6) Specification 56 (§§ 178.251, 178.252 of this subchapter). Metal portable tank. Authorized only for calcium hypochlorite, hydrated; mono-(tri-chloro) tetra-(monopotassium dichloro)-penta-s-triazinetrione, dry; potassium dichloro-s-triazinetrione, dry; sodium dichloro-s-triazinetrione, dry; and trichloro-s-triazinetrione, dry. For rail transportation, see § 174.63(b) of this subchapter.

(8) Specification 12B (§ 178.205 of this subchapter). Fiberboard boxes with inside polyethylene bottles with a minimum wall thickness of 0.015 inch. Not more than 2 polyethylene bottles may be packed in one box and each bottle must not contain more than 20 pounds net weight of the material. Packaging must be such that it will not react dangerously with or be decomposed by the commodity.

9. In § 173.221 paragraph (a)(13) is added to read as follows:

§ 173.221 Liquid organic peroxides, n.o.s., and liquid organic peroxide solutions, n.o.s.

(a) * * *

(13) Specification 57 (§ 178.253 of this subchapter). Metal portable tanks. Tanks are authorized only for tert-butyl cumyl peroxide. The tank may not be filled to more than 90 percent capacity.

10. In § 173.230, paragraph (a)(5) is added to read as follows:

§ 173.230 Sodium, metallic, dispersion in organic solvent.

(a) * * *

(5) Specification 17H (§ 178.118 of this subchapter). Metal drum, with one inside Specification, 5, 5C, 6B, or 6C (§§ 178.80, 178.83, 178.98, 178.99 of this subchapter) closed head metal drum not over 30 gallons capacity. Inside drum must be completely surrounded with incombustible cushioning material.

11. In § 173.245, paragraph (a)(12) is revised to read as follows:

§ 173.245 Corrosive liquids not specifically provided for.

(a) * * *

(12) Specification 12B (§ 178.205 of this subchapter). Fiberboard boxes with inside packagings of metal, polyethylene, or other non-fragile plastic material resistant to the lading, not exceeding 1-gallon each. A metal packaging is authorized only for a material that is not corrosive to metal. Gross weight may not exceed 65 pounds.

12. In § 173.257, paragraph (a)(4) is revised to read as follows:

§ 173.257 Electrolyte (acid) and alkaline corrosive battery fluid.

(a) * * *

(4) Specification MC 310, MC 311, or MC 312 (§ 178.343 of this subchapter). Cargo tanks must be lined with rubber or equally acid-resistant material of equivalent strength and durability. Bottom outlets are authorized if they meet the requirements of § 178.343-5 of this subchapter.

13. In § 173.262, paragraphs (a)(11) and (b)(4) are revised to read as follows:

§ 173.262 Hydrobromic acid.

(a) * * *

(11) Specification MC 310, MC 311, or MC 312 (§ 178.343 of this subchapter). Cargo tanks must be lined with rubber or equally acid-resistant material of equivalent strength and durability. Bottom outlets are authorized if they meet the requirements of § 178.343-5 of this subchapter.

(a) * * *

(4) Specification MC 310, MC 311, or MC 312 (§ 178.343 of this subchapter). Cargo tanks must be lined with rubber or equally acid-resistant material of equivalent strength and durability. Bottom outlets are authorized if they meet the requirements of § 178.353-5 of this subchapter.

14. In § 173.265, paragraph (b)(4) is revised to read as follows:

§ 173.265 Fluosillic acid (hydrofluorosillic acid) (hydrofluosillic acid).

* * * * *

(b) * * *

(4) Specification MC 310, MC 311, or MC 312 (§ 178.343 of this subchapter). Cargo tanks must be lined with rubber or equally acid-resistant material of equivalent strength and durability. Bottom outlets are authorized if they meet the requirements of § 178.343-5 of this subchapter.

* * * * *

15. In § 173.266, paragraphs (f)(1) and the first three sentences of (f)(2) are revised to read as follows:

§ 173.266 Hydrogen peroxide solution in water.

* * * * *

(f) * * *

(1) Specification 103A-ALW, 103CW, 111A60ALW2 or 111A60W7 (§ 179.200, 179.201 of this subchapter). Tank cars. The 103CW and 111A60W7 tank cars must be fabricated of Type 304L, 316, or 316L stainless steel. (See §§ 173.31(a)(4) and 179.3(e) for additional requirements).

* * * * *

(2) Specification MC 310 or MC 312 (§ 178.343 of this subchapter). Cargo tanks. Tanks must be fabricated of aluminum conforming to Aluminum Association Nos. 1060, 1260, 5254, or 5652. Specification MC 312 may be fabricated of Type 304L, 316 or 316L stainless steel. * * *

16. In § 173.272, paragraphs (i)(25) and (i)(28) are revised to read as follows:

§ 173.272 Sulfuric acid.

* * * * *

(i) * * *

(25) Specification MC 310, MC 311, or MC 312 (§ 178.343 of this subchapter). Cargo tanks must be lined with rubber or equally acid-resistant material of equivalent strength and durability.

Bottom outlets are authorized if they meet the requirements of § 178.343-5 of this subchapter.

* * * * *

(28) Specification MC 310, MC 311, or MC 312 (§ 178.343 of this subchapter). Cargo tanks must be lined with rubber or equally acid-resistant material of equivalent strength and durability. Bottom outlets are authorized if they meet the requirements of § 178.343-5 of this subchapter. Not authorized for transportation by vessel.

* * * * *

17. In § 173.301, paragraph (d)(2) is revised to read as follows:

§ 173.301 General requirements for shipment of compressed gases in cylinders:

* * * * *

(d) * * *

(2) Manifolding is authorized for specification cylinders containing the following nonliquefied gases: boron trifluoride, carbon monoxide, ethylene, hydrogen, hydrocarbon gases, methane, nitrogen trifluoride, and tetrafluoroethylene, inhibited, except that aluminum cylinders are not authorized for boron trifluoride or nitrogen trifluoride service. Individual cylinders must be equipped with approved pressure relief devices as required by § 173.34(d) or § 173.315(i) of this Part. Each cylinder must be equipped with an individual shutoff valve that must be tightly closed while in transit. Manifold branch lines of these individual shutoff valves must be sufficiently flexible to prevent damage to the valves which otherwise might result from the use of rigid branch lines. A temperature measuring device may be inserted in one cylinder of a manifold installation in place of the shutoff valve.

* * * * *

18. In § 173.356, paragraph (a)(3) is renumbered (a)(4) and a new paragraph (a)(3) is added to read as follows:

§ 173.356 Thiophosgene.

(a) * * *

(3) Specification 5C (§ 178.83 of this subchapter). Steel barrels or drums made of Type 304 stainless steel.

* * * * *

PART 178—SHIPPING CONTAINER SPECIFICATIONS

§ 178.168-9 [Amended]

19. In § 178.168-9, Group 1 is amended by adding "Mediterranean pine" immediately following the entry "Jack pine".

§ 178.169-9 [Amended]

20. In § 178.169-9, Group 1 is amended by adding "Mediterranean pine" immediately following the entry "Jack pine".

PART 179—SPECIFICATIONS FOR TANK CARS

21. In § 179.101-1(a), Note 4 following the Table is revised to read as follows:

§ 179.101-1 Individual specification requirements.

(a) * * *

At least the upper two-thirds of the exterior of the tank manway nozzle and all appurtenances in contact with this area of the tank shall have a finish coat of white paint; except that tanks used for hydrogen fluoride may have a dark colored band not exceeding 14 feet wide around the center of the tank in the top platform and fitting area.

* * * * *

(49 U.S.C. 1803, 1804, 1808; 49 CFR 1.53. App. A to Part 1).

Issued in Washington, D.C. on March 19, 1985.

L. D. Santman,

Director, Materials Transportation Bureau. [FR Doc. 85-6846 Filed 3-22-85; 8:45 am]

BILLING CODE 4910-60-M